

100 2T

Any 2-Stroke bike, trails, off road bikes, mopeds... fitted with small displacement 2 stroke engines.

TYPE OF USE

Any 2-Stroke bikes, trails, off road bikes, mopeds... fitted with small displacement 2 stroke engines.
Suitable for oil injector systems or premix, leaded or unleaded gasoline.

PERFORMANCES

STANDARDS API TC
 JASO FB Level

Lubricant suitable for all kind of injection systems.
Minimizes deposits on engine internal components and exhaust pipes.
Prevents spark plug from fouling.
Instantaneous and stable mixing with gasoline.

RECOMMENDATIONS

Premix ratio: from 3% to 4% (from 33:1 to 25:1) according to manufacturers' requirements.
Adjust according to your own use.

PROPERTIES

Color	Visual	Green
Density at 20°C (68°F)	ASTM D1298	0.879
Viscosity at 40°C (104°F)	ASTM D445	77.9 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	9.9 mm ² /s
Viscosity Index	ASTM D2270	107.0
Pour point	ASTM D97	15.0 °C / -5.0 °F
Flash point	ASTM D92	166.0 °C / 331.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



100 2T

Any 2-Stroke bike, trails, off road bikes, mopeds... fitted with small displacement 2 stroke engines.

TBN

ASTM D2896

1.2 mg KOH/g