



MOTUL 100 2T

Lubricant for 2 Stroke engines
Lubrication by Oil Injector or Premix
Mineral

TYPE OF USE

Any 2 Stroke bike, trails, off road bikes, mopeds... fitted with small displacement 2 Stroke engines.
Suitable for oil injector systems or premix, using all types of gasoline fuels: leaded or unleaded, with or without Ethanol, biofuels.

PERFORMANCES

Lubricant suitable for all kind of injection systems.
Minimizes deposits on engine internal components and exhaust pipes.
Prevents spark plug from fouling.

Instantaneous and stable mixing with gasoline.

RECOMMENDATIONS

Premix ratio: from 3% to 4% (from 33:1 to 25:1) according to manufacturers' requirements.
Adjust according to your own use.

PROPERTIES

Color	Visual	Green
Density at 20°C (68°F)		0.879
Viscosity at 40°C (104°F)	ASTM D445	77.9 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	9.9 mm²/s
Viscosity Index	ASTM D2270	107.0
Pour point	ASTM D97	-15.0 °C / -5.0 °F
TBN	ASTM D2896	1.2 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com

02/26



MOTUL 100 2T

Lubricant for 2 Stroke engines
Lubrication by Oil Injector or Premix
Mineral

Flash point

ASTM D92

166.0 °C / 331.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com



MOTUL 100 2T

Lubricant for 2 Stroke engines
Lubrication by Oil Injector or Premix
Mineral

STANDARDS	
API	TC
PRODUCTS	
JALOS	FB Level
Steiger	FB Level

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com