



# Multigrade D-Turbo 10W-30

## Diesel Engine Lubricant

### TYPE OF USE

Designed for vehicles powered by diesel engines, including those equipped with Common Rail Direct Injection (CRDI) diesel engines.

Suitable for use in larger engines such as Sports Utility Vehicles (SUV), light-duty trucks, vans and passenger cars requiring a 10W30 viscosity grade and API CH-4 engine oil.

Can also be used in gasoline engines requiring API SL oils.

### PERFORMANCE

PERFORMANCE                      API CH-4/SL

MULTIGRADE D-TURBO provides good lubrication properties to protect engines.

- Its detergency & dispersancy properties effectively prevent harmful deposits and wear, for an optimized engine operation.
- Good resistance against oil thickening to keep engine running smoothly.

### RECOMENDATIONS

Drain interval : according to manufacturers' recommendations and tuned to your own use.  
Can be mixed with synthetic or mineral oils.

### PROPERTIES

Viscosity grade	SAE J 300	<b>10W-30</b>
Density at 20°C (68°F)	ASTM D4052	0.865
Viscosity at 40°C (104°F)	ASTM D445	73.0 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	10.8 mm <sup>2</sup> /s
Viscosity index	ASTM D2270	136
TBN	ASTM D2896	10.2 mg KOH/g