



2100 POWERLIGHT 10W-40

Gasoline and Diesel engine oil

Technosynthese®

TYPE OF USE

Technosynthese® lubricant specially designed for new and old generation engines (Gasoline, Diesel, LPG, Turbocharged and Direct Injection).

Suitable for all type of fuels: leaded or unleaded Gasoline, Ethanol, LPG, Diesel and biofuels. Compatible for catalytic converters.

PERFORMANCES

STANDARDS API SERVICE SM with CF performance
ACEA A3 / B4

PERFORMANCES MB 229.3
VW 502 00 / 505 00

2100 POWERLIGHT 10W40 provides an excellent lubricating properties to extend engine life. It protects engine against wear, helps to reduce friction and keeps engine clean.

Its improved detergency and dispersancy performance prevents harmful deposits and wear for a perfect engine condition. Good anti-oxidation properties to prevent premature oil thickening and ageing due to thermal stress.

Good oil evaporation rate for lower oil consumption.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral oils.

Always refer to the owner manual or handbook of the vehicle.

PROPERTIES

Viscosity grade	SAE J 300	10W-40
Density at 20°C (68°F)	ASTM D1298	0.865
Viscosity at 40°C (104°F)	ASTM D445	101.3 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.9 mm ² /s
Viscosity Index	ASTM D2270	153
Pour point	ASTM D97	-33°C
Flash point	ASTM D92	226°C
TBN	ASTM D2896	10.2 mg KOH/g