

Lubricant for 4 Stroke motorcycle engine **Technosynthese®**

TYPE OF USE

All 4 stroke motorbikes.

Road and off road bikes, Trails, 4 stroke Cross/Enduro bikes, Quads, Scooters, Mopeds...

PERFORMANCES

STANDARDS **API SM** PERFORMANCES JASO MA2

Formulated with a balance additive chemistry that guarantees rider's satisfaction with the following enhance performances:

- High detergent and dispersant properties to maintain engine cleanliness and excellent deposit control
- Unique additive technology for engine & catalyst durability
- Anti-wear technology to ensure engine and gear wear protection in motorcycle
- Provides clutch friction durability
- Outstanding oxidation resistance
- Excellent corrosion resistance

JASO MA2 high friction performance ensures the perfect clutch lock up at start-up, acceleration and full speed.

Easy gear shifting.

RECOMMENDATIONS

Oil change: follow the manufacturers' recommendations and to be adjusted according to the using condition. Can be mixed with synthetic or mineral lubricants.

PROPERTIES

Viscosity grade	SAE J 300	10W-40
Density at 20°C (68°F)	ASTM D1298	0.859
Viscosity at 40°C (104°F)	ASTM D445	99.2 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.4 mm ² /s
Viscosity Index	ASTM D2270	150
Pour point	ASTM D97	-33°C
Flash point	ASTM D92	224°C
TBN	ASTM D2896	6.1 mg KOH/g