



# 3100 GOLD 4T 15W50

Lubricant for 4 Stroke motorcycle engine

Technosynthese®

## TYPE OF USE

All 4 stroke motorbikes.

Road and off road bikes, Trails, 4 stroke Cross/Enduro bikes, Quads, Scooters, Mopeds...

## PERFORMANCES

STANDARDS                      API SM  
PERFORMANCES                JASO MA2

Formulated with a balance additive chemistry that guarantees rider's satisfaction with the following enhance performances:

- High detergent and dispersant properties to maintain engine cleanliness and excellent deposit control
- Unique additive technology for engine & catalyst durability
- Anti-wear technology to ensure engine and gear wear protection in motorcycle
- Provides clutch friction durability
- Outstanding oxidation resistance
- Excellent corrosion resistance

JASO MA2 high friction performance ensures the perfect clutch lock up at start-up, acceleration and full speed.

Easy gear shifting.

## RECOMMENDATIONS

Oil change: follow the manufacturers' recommendations and to be adjusted according to the using condition. Can be mixed with synthetic or mineral lubricants.

## PROPERTIES

Viscosity grade	SAE J 300	<b>15W-50</b>
Density at 20°C (68°F)	ASTM D1298	0.864
Viscosity at 40°C (104°F)	ASTM D445	144.2 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	18.6 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	145
Pour point	ASTM D97	-30°C
Flash point	ASTM D92	230°C
TBN	ASTM D2896	6.2 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 – Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79. Web Site: [www.motul.com](http://www.motul.com)