



MOTUL 300V TROPHY 0W-40

DESCRIPTION

All racing Gasoline or Diesel engines, naturally aspirated or turbocharged, fitted with injection (direct/indirect) or carburetted.

For race prepared engines operating over a wide range of rpm and temperatures.

APPLICATIONS

TYPE OF USE Rally – GT – Short distance race

The SAE 0W-40 viscosity allows excellent oil flow into the engine at start-up and fast oil pressure establishment while guaranteeing at hot temperature high oil pressure for outstanding protection and faster engine revving.

ESTER Core® TECHNOLOGY

For decades MOTUL has developed high performance synthetic Ester based lubricants.

By selecting esters over other high performance synthetic base stocks and combining them with an innovative additive package, MOTUL has created a perfect synergy.

This most advanced **ESTER Core®** Technology allows maximum power output of the engine without compromising reliability and wear.

ADVANTAGES

The SAE 0W-40 viscosity enables to compensate medium engine oil dilution by unburned fuel and maintains a stable oil pressure.

Maximum oil film resistance at very high temperature: Engine wear is reduced.

Friction Modifier: Maximum power output, decrease operating temperature.

Low volatility: Oil consumption is reduced.

High shear stability: Stable oil pressure whatever using conditions.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.