

4000 MOTION 10W-30**Gasoline or Diesel Engine Oil
"Fuel Economy" performance****TYPE OF USE**

Specially designed for vehicles requiring SAE 10W-30 viscosity oil, low HTHS and Fuel Economy performances. Suitable for all types of Gasoline engines, with injection or carburetor, and catalytic converter. Suitable for all type of fuel. These oils may be unsuitable for use in some engines. Refer to the owner manual or handbook if in doubt.

PERFORMANCES

STANDARDS ACEA A1 / B1
 API SL / CF

The new performance ACEA A1/B1 requires fuel economy and low emission performance for engines. MOTUL 4000 Motion 10W-30 reduces friction in the engine. Detergent, dispersive agents and anti-oxidation additives are particularly reinforced to resist over extended oil change required by manufacturers for new car models. Very efficient anti-deposit and anti-black sludge properties to help maintaining the engine clean. Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use. MOTUL 4000 Motion 10W30 can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	10W-30
Density at 20°C (68°F)	ASTM D1298	0.867
Viscosity at 40°C (104°F)	ASTM D445	81.0 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	12.1 mm ² /s

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



4000 MOTION 10W-30

Gasoline or Diesel Engine Oil
"Fuel Economy" performance

Viscosity Index	ASTM D2270	145.0
Pour point	ASTM D97	-27.0 °C / -16.0 °F
Flash point	ASTM D92	220.0 °C / 428.0 °F
TBN	ASTM D2896	8.8 mg KOH/g