



MOTUL 4000 MOTION 15W-40

Petrol and Diesel engine oil
Mineral

TYPE OF USE

Specially designed for cars powered by petrol and Diesel engines, naturally aspirated or turbocharged, indirect or direct injection, carburetor or injection, with or without catalytic converter.

Suitable for all type of fuels: leaded or unleaded petrol, Ethanol, LPG, Diesel and biofuels.

PERFORMANCES

The standard API SN is more stringent than API SM and SL in terms of ageing resistance (average drain interval increased), requires anti-oxidation properties that maintain a constant viscosity avoiding sludge and deposits in the crank-case, anti-wear properties and dispersant power.

Detergent, dispersive agents and anti-oxidation additivation are particularly reinforced to ensure longer drain intervals, required by manufacturers for the new model of cars.

Very efficient anti-deposit and anti-black sludge power which maintains a clean engine.

Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.

MOTUL 4000 Motion 15W-40 can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	15W-40
Density at 20°C (68°F)		0.869
Viscosity at 40°C (104°F)	ASTM D445	113.2 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.8 mm ² /s
Viscosity Index	ASTM D2270	135.0
Pour point	ASTM D97	-42.0 °C / -44.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com



MOTUL 4000 MOTION 15W-40

Petrol and Diesel engine oil
Mineral

TBN	ASTM D2896	9.8 mg KOH/g
Flash point	ASTM D92	238.0 °C / 460.0 °F



MOTUL 4000 MOTION 15W-40

Petrol and Diesel engine oil
Mineral

STANDARDS	
ACEA	A3/B3
API	SERVICE SN
MERCEDES-BENZ	MB-Approval 229.1

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com

