



## 4100 MULTI D 10W40

**Diesel and Turbo Diesel Engine Oil**  
**API CF Certified**  
**Technosynthese®**

### TYPE OF USE

Specially designed for Diesel engine car.  
All Diesel and Turbo Diesel engines, recent or older.

### PERFORMANCES

STANDARDS	ACEA B3 API CF
APPROVALS	MERCEDES-BENZ MB-Approval 229.1
PERFORMANCES	VW 505 00

API, Volkswagen and Mercedes official approvals guarantee the quality of the product conception and manufacture.

SAE 10W-40 viscosity grade is totally adapted to Diesel engines and ensures easier starts.

The synthetic base gives a very high lubricating power which reduces frictions and ensures a resistance to very high temperatures reached in modern engines.

Anti-oxidation, Anti-wear, Anti-corrosion, Anti-foam.

### RECOMMENDATIONS

Drain period : according to manufacturers' recommendations and to be adjusted according to your own use.  
MOTUL 4100 can be mixed with synthetic or mineral oils.

### PROPERTIES

Viscosity grade	SAE J 300	10W-40
Density at 20°C (68°F)	ASTM D1298	0.874
Viscosity at 40°C (104°F)	ASTM D445	95.0 mm <sup>2</sup> /s

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



## 4100 MULTI D 10W40

**Diesel and Turbo Diesel Engine Oil**  
**API CF Certified**  
**Technosynthese®**

Viscosity at 100°C (212°F)	ASTM D445	14.8 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	163.0
Pour point	ASTM D97	-33.0 °C / -27.0 °F
TBN	ASTM D2896	8.0 mg KOH/g
Flash point	ASTM D92	228.0 °C / 442.0 °F