



MOTO 4T 10W50

Lubricant for 4 Stroke motorcycle engine

Mineral

TYPE OF USE

All 4 stroke motorbikes.

PERFORMANCES

STANDARDS	API SJ
Performance	JASO MA2

Good lubricating properties which decrease friction and wear for engine, gear and clutch protection for everyday use.

Strong dispersant and detergent properties to ensure engine cleanliness and deposit control.

Excellent shear resistance and oil film thickness to protect gears and ensure engine durability.

JASO MA2 ensure the perfect clutch lock up at start-up, acceleration and full speed.

Easy gear shifting.

RECOMMENDATIONS

Oil change: follow the manufacturers' recommendations and to be adjusted according to use condition.
Can be mixed with synthetic or semi synthetic lubricants.

PROPERTIES

Viscosity grade	SAE J 300	10W-50
Density at 20°C (68°F)	ASTM D1298	0.859
Viscosity at 40°C (104°F)	ASTM D445	127.4 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	17.9 mm²/s
Viscosity Index	ASTM D2270	156
Pour point	ASTM D97	-33°C
Flash point	ASTM D92	238°C
TBN	ASTM D2896	5.3 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 – Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79. Web Site : www.motul.com

08/20