



MULTIPOWER 15W-50

Gasoline and Diesel Engine Oil

Technosynthese®

TYPE OF USE

Designed for passenger cars equipped with gasoline or diesel engines, turbo or naturally aspirated.

Suitable for standard and unleaded fuel.

All driving conditions : City, Road, Highway.

PERFORMANCE

STANDARDS API SM with CF performance

Excellent performing anti-wear additives to reduce internal frictions and increasing engine life duration.

Adapted viscosity for all types of engines working under tropical conditions.

Lower oil consumption due to the low volatility.

Very efficient detergent power for a better engine cleanliness.

Maximum protection at high temperatures to avoid oxidation phenomenon.

Compatible with catalytic converters.

Anti-corrosion, Anti-foam properties.

RECOMENDATIONS

Drain period : according to manufacturers' recommendations and tune to your own use.

MOTUL MUTIPOWER 15W-50 can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	15W-50
Density at 20°C (68°F)	ASTM D4052	0.863
Viscosity at 40°C (104°F)	ASTM D445	145.1 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	19.0 mm ² /s
Viscosity index	ASTM D2270	149
TBN	ASTM D2896	7.2 mg KOH/g