

# DATA L U L

## **MOTUL 5100 OFF ROAD 10W-40 4T**

#### SYNTHETIC BASE

#### DESCRIPTION

Street & road bikes, trails, off road bikes, enduro, trial...fitted with 4 Stroke engines, integrated gearbox or not, wet or dry clutch, engines meeting Euro 2 or Euro 3 emission regulation, fitted with exhaust gas after treatment systems: catalytic converters, air injection into exhaust pipe... Suitable for specific SUZUKI, YAMAHA, KAWASAKI engines requiring SAE 10W-40 viscosity grade oil.

Other uses: street bikes without catalytic converters, scooters, ATVs, UTVs...

#### **APPLICATIONS**

STANDARDS: API SM / SL / SJ / SH / SG

SPECIFICATIONS: JASO MA2 under N° M033MOT112

#### Protection

Technosynthese® lubricant reinforced by Ester base stock to warranty anti-wear properties and improve gear protection and lifetime.

Improved oil film resistance at high temperatures for engine durability.

Optimized Phosphorus and Sulphur content (JASO MA2 < 1200 ppm) for better operating conditions of catalytic converters.

The innovative anti wear additives package provides excellent gearbox protection. FZG Gear Test results: Pass FLS 14. The FZG (Forschungsstelle für Zahnrader und Getriebebau) Test, evaluates fluid lubricating and wear protection properties at the interface of a loaded set of gears.

#### Comfort

JASO has created its own 4-stroke motorcycle standard -JASO T903- which has three grades MA, MA1 and MA2.

JASO MA2 offers the most efficient friction levels to guarantee the clutch engagement during the three riding modes: Starting, Acceleration and Constant Speed.

#### SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.



### **DATA**



SHEET

#### Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.