



MOTUL 5100 15W-50 4T VL

SYNTHETIC BASE

DESCRIPTION

Technosynthese® Ester based high performance motorcycle lubricant for street & road bikes, trails, off road bikes, enduro, trial fitted with 4-stroke engines, integrated or non-integrated gearbox, wet or dry clutch, engines meeting Euro 2 or Euro 3 emission regulations, fitted with exhaust gas after treatment systems: catalytic converters, air injection into exhaust pipe. Recommended for specific BMW, DUCATI engines requiring SAE 15W-50 viscosity grade oil. Other uses: street bikes without catalytic converters, ATVs, UTVs.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.