



Scooter Expert LE 4T 10W30

4 stroke scooter engine oil

Technosynthese® – JASO MB – Low Emission

TYPE OF USE

Specifically designed for 4 stroke engine of powerful and recent scooters for which manufacturer recommends JASO MB specification, with or without catalytic converters, without wet clutch.

Suitable for all type of gasoline fuels, leaded or unleaded, biofuels.

PERFORMANCE

STANDARDS API SM
APPROVAL JASO MB

Technosynthese® engine oil, reinforced with synthetic base stocks which provide outstanding protection and oil film resistance. Formulation is perfectly balanced to provide excellent control of piston deposit, wear and bearing corrosion. Good detergency to help maintain engine cleanliness. Good anti-oxidation properties to prevent premature ageing of oil.

SAE 10W-30 viscosity grade improves cold engine start and contributes to fuel economy. JASO MB lubricant ensures optimal scooter performance and fuel economy.

RECOMMENDATIONS

Oil change : according to manufacturers' recommendations and to be adjusted according to particular use. Can be mixed with synthetic or mineral lubricants.

MOTUL Scooter Expert LE 4T 10W30 cannot be used to the system that requires JASO MA specification.

PROPERTIES

Viscosity grade	SAE J 300	10W-30
Density at 15°C (59°F)	ASTM D1298	0.860
Viscosity at 40°C (104°F)	ASTM D445	77.6 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	11.5 mm ² /s
Viscosity index	ASTM D2270	141
Pour point	ASTM D97	-33°C
Flash point	ASTM D92	228°C
TBN	ASTM D2896	6.2 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. Made in France
MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79. WebSite: www.motul.fr