



Specific CRDi Diesel 5W-40

Diesel and Gasoline Engine Lubricant

100% Synthetic

TYPE OF USE

Specially designed for new generation cars equipped with Common Rail Direct Injection diesel engines. Suitable for turbo or naturally aspirated diesel engines, with catalytic converters.

Also suitable for gasoline engines.

PERFORMANCE

STANDARDS ACEA A3/B4
API SN with CF performance

ACEA B4 performance provides an outstanding detergent/dispersant performance to deal with additional soot/deposits produced by Direct Injection Diesel engines.

SPECIFIC CRDi Diesel 5W-40 also provides excellent lubrication properties and reduced volatility. It is especially formulated to provide protection on modern engines operating at high temperatures. Powerful in maintaining engine cleanliness from modern detergent and dispersant technology. Excellent anti-wear, anti-corrosion and anti-foam properties.

RECOMENDATIONS

Drain interval : according to manufacturers' recommendations and tuned to your own use.

MOTUL Specific CRDi Diesel can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	5W-40
Density at 15°C (68°F)	ASTM D4052	0.853
Viscosity at 40°C (104°F)	ASTM D445	85.1 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.0 mm ² /s
Viscosity index	ASTM D2270	170
TBN	ASTM D2896	10.8 mg KOH/g