

**Extended Fuel Economy oil for Petrol & Hybrid Petrol engines
Technosynthese®**

TYPE OF USE

High Performance synthetic Technosynthese® engine lubricant for extended Fuel Economy.

Specially designed for recent vehicles powered by petrol & Hybrid petrol engines, naturally aspirated or turbocharged, indirect or direct injection, requiring use of a "Fuel Economy" low friction and low HTHS (High Temperature High Shear) viscosity oil (≥ 2.9 mPa.s).

Suitable for modern petrol engines requiring a viscosity grade 30 and fuel economy lubricant (API SP and/or ILSAC GF-6A standard).

Improves fuel economy, engine response and protects against the risks of LSPI (Low Speed Pre-Ignition) abnormal combustions.

Compatible with catalytic converters.

This type of oil may be unsuitable for use in some engines. Refer to the owner manual if in doubt.

PERFORMANCES

The API SP standard is fully backward compatible over API SN standard and all former API standards.

API SP lubricants provide outstanding oxidation resistance, better anti-deposits protection, better engine cleanliness, anti-wear protection and enhanced performance at cold temperature for Fuel Economy savings during the whole oil life span.

Turbocharged petrol engines with direct injection have a certain risk of sporadic pre-ignition phenomena in the combustion chambers. This type of sporadic abnormal combustion called LSPI for Low Speed Pre-Ignition generates very high pressure peaks in the combustion chamber that can lead to piston damages and ultimately to engine destruction. The API SP standard now fully covers this LSPI requirement in order to perfectly protect direct injection turbocharged petrol engines.

Based on the API SP specification, the ILSAC GF-6A standard is even more severe especially on the energy saving criteria. The requirements on the low viscosity "Fuel Economy" side of the lubricant, but also extended drain intervals, clean pistons/rings, seals compatibility and reduced content of phosphorus for after treatment systems compatibility are enhanced. The ILSAC GF-6A specification ensures perfect engine protection when petrol containing up to 85% Ethanol is used (E85).

MOTUL 6100 SAVE-lite 5W-30 provides high lubricating properties such as wear protection and high temperature resistance for better controlled oil consumption, improves oil flow at start up for faster oil pressure build up, faster rev raisings, faster operating temperature reach and extended fuel economy benefits.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com



MOTUL 6100 SAVE-LITE 5W-30

**Extended Fuel Economy oil for Petrol & Hybrid Petrol engines
Technosynthese®**

Environment friendly, this type of oil allows fuel consumption reduction and therefore minimizes greenhouse gases (CO₂) emissions.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.
MOTUL 6100 SAVE-lite 5W-30 can be mixed with synthetic or mineral oils.
Before use always refer to the owner manual or handbook of the vehicle.

PROPERTIES

Viscosity grade	SAE J 300	5W-30
Density at 20°C (68°F)	ASTM D1298	0.856
Viscosity at 40°C (104°F)	ASTM D445	63.3 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	10.5 mm ² /s
HTHS viscosity at 150°C (302°F)	ASTM D4741	3.2 mPa.s
Viscosity Index	ASTM D2270	156.0
Pour point	ASTM D97	-45.0 °C / -49.0 °F
Sulfated Ash	ASTM D874	mm ² /s 0.72
TBN	ASTM D2896	7.2 mg KOH/g
Flash point	ASTM D92	230.0 °C / 446.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com



MOTUL 6100 SAVE-LITE 5W-30

Extended Fuel Economy oil for Petrol & Hybrid Petrol engines
Technosynthese®

STANDARDS	
API	PERFORMANCE SP
ILSAC	GF-6A

