



# 7000 4T 10W-30

**Lubricant for 4-Stroke Motorcycle Engine  
Sport & Commuting  
100% Synthetic**

## TYPE OF USE

All 4-Stroke Motorbikes.

Road and Off Road Bikes, Trails, 4-Stroke Cross/Enduro Bikes, Quads, Scooters, Mopeds...

## PERFORMANCES

STANDARDS                      API SP  
SPECIFICATION                JASO MA2 under N° M065MOT223

100% Synthetic lubricant for improved oil film resistance at high temperatures and high revolutions. Excellent temperature resistance against oxidation to avoid premature oil thickening. Special additive technology provides good friction properties, deposit and wear protection for increased engine life. Anti-wear technology provides outstanding gearbox durability. High detergent & dispersant properties for a clean and durable engine.

JASO MA2 high friction performance ensures the perfect clutch lock up at start-up, acceleration and full speed.  
Easy gear shifting.

## RECOMMENDATIONS

Oil change: follow the manufacturers' recommendations and to be adjusted according to the using condition. Can be mixed with synthetic or mineral lubricants.

## PROPERTIES

Viscosity grade	SAE J 300	<b>10W-30</b>
Density at 20°C (68°F)	ASTM D4052	0.847
Viscosity at 40°C (104°F)	ASTM D445	84.3 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	11.6 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	152
Pour point	ASTM D97	-41°C
Flash point	ASTM D92	250°C
TBN	ASTM D2896	6.5 mg KOH/g