



7000 4T 10W-40

**Lubricant for 4-Stroke Motorcycle Engine
Sport & Commuting
100% Synthetic**

TYPE OF USE

All 4-Stroke Motorbikes.

Road and Off Road Bikes, Trails, 4-Stroke Cross/Enduro Bikes, Quads, Scooters, Mopeds...

PERFORMANCES

STANDARDS	API SP
SPECIFICATION	JASO MA2 under N° M065MOT224

100% Synthetic lubricant for improved oil film resistance at high temperatures and high revolutions. Excellent temperature resistance against oxidation to avoid premature oil thickening. Special additive technology provides good friction properties, deposit and wear protection for increased engine life. Anti-wear technology provides outstanding gearbox durability. High detergent & dispersant properties for a clean and durable engine.

JASO MA2 high friction performance ensures the perfect clutch lock up at start-up, acceleration and full speed.
Easy gear shifting.

RECOMMENDATIONS

Oil change: follow the manufacturers' recommendations and to be adjusted according to the using condition. Can be mixed with synthetic or mineral lubricants.

PROPERTIES

Viscosity grade	SAE J 300	10W-40
Density at 20°C (68°F)	ASTM D4052	0.849
Viscosity at 40°C (104°F)	ASTM D445	98.5 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	14.9 mm²/s
Viscosity Index	ASTM D2270	159
Pour point	ASTM D97	-40°C
Flash point	ASTM D92	252°C
TBN	ASTM D2896	6.5 mg KOH/g