



MOTUL 7100 10W-30 4T

**High Performance Motorcycle Lubricant
Sport & Adventure
Synthetic Technology**

TYPE OF USE

Synthetic technology 4-Stroke lubricant – Ester technology - Meets bike manufacturer specifications, especially HONDA which recommends SAE 10W30 for fuel economy improvement. Smooth shifting. Improved shear resistance. Meets JASO MA2 specifications for optimal wet clutch performance. Suitable for catalytic converters.

PERFORMANCES

STANDARDS API SP
JASO MA2 (2023) No. M033MOT211

Protection

Ester Technology:

- Low traction coefficient Ester to minimize engine internal friction losses and improve performance.
 - Synergy of Ester with anti-wear additives and improved shear resistance for improved gear protection and life time.
- 100% Synthetic lubricant for improved oil film resistance at high temperatures and high revs.
Optimized Phosphorus and Sulfur content (JASO MA2 < 1200 ppm) for better operating conditions of catalytic converters.
The innovative anti-wear additives package provides outstanding gearbox protection. FZG Gear Test results: Pass FLS>14. The **FZG (Forschungsstelle für Zahnrad und Getriebebau)** Test, evaluates fluid lubricating and wear protection properties at the interface of a loaded set of gears. Lubricants are then graded based on their “Failure Load Stage” or FLS rating from FLS 1 (very poor result) up to FLS 14 (outstanding result).

Comfort

JASO has created its own 4-stroke motorcycle standard -JASO T903- which has three grades MA, MA1 and MA2. JASO MA2 offers the most efficient friction levels to guarantee the clutch engagement during the three riding modes: Starting, Acceleration and Constant Speed.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.
Can be mixed with synthetic or mineral lubricants.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL Deutschland GmbH - Butzweilerhofallee 3 - 50829 - Köln - +49(0)221/67003-0 - +49(0)221/67003-199 - info@motul.de - http://www.motul.com

motul.com



MOTUL 7100 10W-30 4T

**High Performance Motorcycle Lubricant
Sport & Adventure
Synthetic Technology**

PROPERTIES

Color	Visual	Red
Viscosity grade	SAE J 300	10W-30
Density at 20°C (68°F)	ASTM D1298	0.851
Viscosity at 40°C (104°F)	ASTM D445	65.2 mm ² /s
	ASTM D445	10.5 mm ² /s
Viscosity at 100°C (212°F)		
HTHS viscosity at 150°C (302°F)	ASTM D4741	3.2 mPa.s
Viscosity Index	ASTM D2270	150.0
	ASTM D97	-33.0 °C / -27.0 °F
Pour point		
Flash point	ASTM D92	236.0 °C / 457.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.