

Yüksek Performanslı 2 zamanlı motor yağı
High Performance 2 stroke engine lubricant
Lubrication by Oil Injector or Premix
Synthese-Technologie - ESTER - Anti-Smoke

TYPE OF USE

Any high performance 2 Stroke bikes, sports bikes, replicas, trails, off road bikes, enduro, mopeds... fitted with high performance 2 Stroke engines, running at high rpm in severe conditions, direct injection or carburetor. Suitable for oil injector systems or premix, using all types of gasoline fuels: leaded or unleaded, with or without Ethanol, biofuels.
Compatible with catalytic converters.
Other uses: Scooters, ATV...

PERFORMANCES

STANDARDS API TC
 ISO -L-EGD

PERFORMANCES JALOS FD under N° 033MOT070

Synthese-Technologie lubricant, Ester technology, specially engineered for high performance engines running at high rpm, perfect oil film resistance to protect against wear.

Improved power output by minimizing engine internal friction.

The international Japanese JASO Fx standard consists in passing 4 engine bench tests in order to evaluate lubricity, detergency, anti-smoke and anti-deposit 2T lubricant properties. JASO FD performance is the highest level of JASO standard and brings improved engine cleanliness compared to JASO FC.

Formulation built on Ester and Synthetic base stocks with very high combustion properties which minimizes smoke and deposits.

Instantaneous and stable mixing with gasoline.

RECOMMENDATIONS

Mixing ratio: from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements.

Adjust according to your own use.

MOTUL**710 2T**

Yüksek Performanslı 2 zamanlı motor yağı
High Performance 2 stroke engine lubricant
Lubrication by Oil Injector or Premix
Synthese-Technologie - ESTER - Anti-Smoke

PROPERTIES

| Couleur | Visuelle | Vert |
|---------------------------|------------|-------------------------|
| Densité à 20°C | ASTM D1298 | 0.880 |
| Viscosité à 40°C (104°F) | ASTM D445 | 70.0 mm ² /s |
| Viscosité à 100°C (212°F) | ASTM D445 | 11.0 mm ² /s |
| Indice de viscosité | ASTM D2270 | 148.0 |
| Point éclair | ASTM D92 | 154.0 °C / 309.0 °F |
| TBN | ASTM D2896 | 2.4 mg KOH/g |

Motul 2/2 TECHNICAL DATA SHEET

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br\>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 -

motul.com

12/20