



TWIN SYN 20W50

Oil for 4 stroke motorcycle engine

Technosynthese®

TYPE OF USE

All 4-stroke V-Twin engine for on-road and off-road bikes.

PERFORMANCE

STANDARDS API SL
APPROVAL JASO MA under N° M065MOT025

Excellent anti-oxidation preventing premature oil thickening and ageing due to high temperature stress.
High lubricating properties which decrease friction and wear and increase engine life.
High detergent and dispersive properties.
Anti-corrosion, anti-foam properties.

RECOMMENDATIONS

Oil change : according to manufacturers' recommendations and tune to your own use.
MOTUL Twin Syn 20W-50 can be mixed with synthetic or mineral lubricants.

PROPERTIES

Viscosity grade	SAE J 300	20W-50
Density at 20 °C (68 °F)	ASTM D1298	0.881
Viscosity at 40 °C (104 °F)	ASTM D445	168.1 mm ² /s
Viscosity at 100 °C (212 °F)	ASTM D445	18.9 mm ² /s
Viscosity index	ASTM D2270	127
Pour point	ASTM D97	-30 °C
Flash point	ASTM D92	230 °C
TBN	ASTM D 2896	6.7 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 – Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79. Web Site: www.motul.fr