



## MOTUL 800 FACTORY LINE OFF ROAD 2T

**Racing Lubricant for Motocross / MX  
Premix Racing 2 stroke Engines  
Synthetic Technology**

### TYPE OF USE

Synthetic technology 2-Stroke motorcycle racing lubricant developed for Factory Teams. 800 Factory Line lubricant takes advantage of the **ESTER** Core® Technology to ensure you maximum power output of the engine without compromising the reliability and the wear. By selecting esters over other high performance synthetic base stocks and combining them with an innovative additive package, MOTUL has created a perfect synergy dedicated to the engine.

### PERFORMANCES

STANDARDS Above existing standards / Lubricant used by major team's for MOTOCROSS GRAND PRIX

#### **ESTER** Core® **TECHNOLOGY**

For decades MOTUL has developed high performance synthetic Ester based lubricants.

By selecting esters over other high performance synthetic base stocks and combining them with an innovative additive package, MOTUL has created a perfect synergy.

This most advanced **ESTER** Core® TECHNOLOGY allows maximum power output of the engine without compromising reliability and wear.

Very high lubricating properties which decrease friction and wear.

Improved formulation: Reinforced desmulsion properties: prevents carburettor throttle from sticking and provides a perfect lubrication under wet conditions.

Keeps engines and exhaust power valves always well lubricated.

Prevents piston rings and exhaust power valves from sticking.

Red coloured: can be easily detected in fuel.

### RECOMMENDATIONS

Mixing ratio: MOTO CROSS GRAND PRIX: 2% (50:1). In normal conditions decrease the percentage by 0.5%.

Tune according to your own use.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL Deutschland GmbH - Butzweilerhofallee 3 - 50829 - Köln - +49(0)221/67003-0 - +49(0)221/67003-199 - info@motul.de - http://www.motul.com

**motul.com**



## MOTUL 800 FACTORY LINE OFF ROAD 2T

Racing Lubricant for Motocross / MX  
Premix Racing 2 stroke Engines  
Synthetic Technology

### PROPERTIES

Color	Visual	Red
Density at 20°C (68°F)		0.911
	ASTM D445	120.2 mm <sup>2</sup> /s
Viscosity at 40°C (104°F)		
	ASTM D445	15.5 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)		
	ASTM D2270	135.0
Viscosity Index		
Flash point	ASTM D92	252.0 °C / 485.6 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

06/24