

**MOTUL 800 FACTORY LINE ROAD
RACING 2T****DESCRIPTION**

Formula developed for Road Racing Grand Prix Teams. Suitable for all kind of gasoline up to 124 octane.

All racing premix 2 Stroke engines fitted on Racing bikes and operating at high revs and under high load.

For moto-cross, use MOTUL 800 2T OFF ROAD.

For oil injector systems, use MOTUL 710 2T.

APPLICATIONS**ESTER Core® TECHNOLOGY**

For decades MOTUL has developed high performance synthetic Ester based lubricants.

By selecting esters over other high performance synthetic base stocks and combining them with an innovative additive package, MOTUL has created a perfect synergy.

This most advanced **ESTER** Core® TECHNOLOGY allows maximum power output of the engine without compromising reliability and wear.

Allow a perfect lubrication when running on wet weather conditions.

Very high lubricating properties for low friction and wear.

Keeps engines and exhaust power valves clean and well lubricated.

Prevents piston rings and exhaust power valves from sticking.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.