



MOTUL 800 FACTORY LINE OFF ROAD 2T

Motocross / MX için yarış yağı
Racing Lubricant for Motocross / MX
Premix Racing 2 stroke Engines
Synthetic Technology

TYPE OF USE

Formula developed for Motocross Grand Prix Teams. Suitable with standard and unleaded gasoline up to 124 octane. All racing 2 stroke engines, high performance and using premix: Motocross, Enduro, Trials, Quads, Watercrafts, ... For road bikes, use MOTUL 800 2T ROAD RACING. For oil injector systems, use MOTUL 710 2T.

PERFORMANCES

STANDARDS Above existing standards / Lubricant used by major team's for MOTOCROSS GRAND PRIX

ESTER Core® TECHNOLOGY

For decades MOTUL has developed high performance synthetic Ester based lubricants.

By selecting esters over other high performance synthetic base stocks and combining them with an innovative additive package, MOTUL has created a perfect synergy.

This most advanced **ESTER Core®** Technology allows maximum power output of the engine without compromising reliability and wear.

Very high lubricating properties which decrease friction and wear.

Improved formulation: Reinforced desemulsion properties: prevents carburettor throttle from sticking and provides a perfect lubrication under wet conditions.

Keeps engines and exhaust power valves always well lubricated.

Prevents piston rings and exhaust power valves from sticking.

Red coloured: can be easily detected in fuel.

RECOMMENDATIONS

Mixing ratio: MOTO CROSS GRAND PRIX: 2% (50:1). In normal conditions decrease the percentage by 0.5%.
Tune according to your own use.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL Deutschland GmbH - Butzweilerhofallee 3 - 50829 - Köln - +49(0)221/67003-0 - +49(0)221/67003-199 - info@motul.de - http://www.motul.com

motul.com



MOTUL 800 FACTORY LINE OFF ROAD 2T

Motocross / MX için yarış yağı
Racing Lubricant for Motocross / MX
Premix Racing 2 stroke Engines
Synthetic Technology

PROPERTIES

Color	Visual	Red
Density at 20°C (68°F)		0.911
	ASTM D445	120.2 mm ² /s
Viscosity at 40°C (104°F)		
	ASTM D445	15.5 mm ² /s
Viscosity at 100°C (212°F)		
	ASTM D2270	135.0
Viscosity Index		
Flash point	ASTM D92	252.0 °C / 486.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.