

800 2T FL ROAD DE

Yol Yarışı Grand Prix Yağlayıcısı Road Racing Grand Prix Lubricant Premix Racing 2 stroke Engines Synthese-Technologie - *ESTER* Core[®] Technology

TYPE OF USE

Formula developed for Road Racing Grand Prix Teams. Suitable for all kind of gasoline up to 124 octane.

All racing premix 2 stroke engines fitted on Racing bikes and operating at high revs and under high load.

For moto-cross, use MOTUL 800 2T OFF ROAD. For oil injector systems, use MOTUL 710 2T.

PERFORMANCES

STANDARDS

Above All Standards

ESTER Core® TECHNOLOGY

For decades MOTUL has developed high performance synthetic Ester based lubricants.

By selecting esters over other high performance synthetic base stocks and combining them with an innovative additive package, MOTUL has created a perfect synergy.

This most advanced *ESTER* Core® Technology allows maximum power output of the engine without compromising reliability and wear.

Allow a perfect lubrication when running on wet weather conditions.

Very high lubricating properties for low friction and wear.

Keeps engines and exhaust power valves clean and well lubricated.

Prevents piston rings and exhaust power valves from sticking.

RECOMMENDATIONS

Mixing ratio: ROAD RACING GRAND PRIX from 3% to 4% (from 33:1 to 25:1)

In normal conditions decrease the percentage by 0.5%.

Adjust according to your own use.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br/>
Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE
MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



800 2T FL ROAD DE

Yol Yarışı Grand Prix Yağlayıcısı Road Racing Grand Prix Lubricant Premix Racing 2 stroke Engines Synthese-Technologie - *ESTER* Core[®] Technology

PROPERTIES

Color	Visual	Orange	
Density at 20°C (68°F)	ASTM D1298	0.926	
Viscosity at 40°C (104°F)	ASTM D445	152.0 mm²/s	
Viscosity at 100°C (212°F)	ASTM D445	18.7 mm²/s	
Viscosity Index	ASTM D2270	140.0	
Flash point	ASTM D92	274.0 °C / 525.0 °F	

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br/>
Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com