

800 2T FL ROAD RACING

**Yol Yarışı Grand Prix Yağlayıcısı
Road Racing Grand Prix Lubricant
Premix Racing 2 stroke Engines
Synthese-Technologie - *ESTER* Core® Technology**

TYPE OF USE

Formula developed for Road Racing Grand Prix Teams. Suitable for all kind of gasoline up to 124 octane.
All racing premix 2 stroke engines fitted on Racing bikes and operating at high revs and under high load.
For moto-cross, use MOTUL 800 2T OFF ROAD. For oil injector systems, use MOTUL 710 2T.

PERFORMANCES**STANDARDS*****ESTER* Core® TECHNOLOGY**

For decades MOTUL has developed high performance synthetic Ester based lubricants.

By selecting esters over other high performance synthetic base stocks and combining them with an innovative additive package, MOTUL has created a perfect synergy.

This most advanced *ESTER* Core® Technology allows maximum power output of the engine without compromising reliability and wear.

Allow a perfect lubrication when running on wet weather conditions.

Very high lubricating properties for low friction and wear.

Keeps engines and exhaust power valves clean and well lubricated.

Prevents piston rings and exhaust power valves from sticking.

RECOMMENDATIONS

Mixing ratio: ROAD RACING GRAND PRIX from 3% to 4% (from 33:1 to 25:1)

In normal conditions decrease the percentage by 0.5%.

Adjust according to your own use.



800 2T FL ROAD RACING

Yol Yarışı Grand Prix Yağlayıcısı
Road Racing Grand Prix Lubricant
Premix Racing 2 stroke Engines
Synthese-Technologie - *ESTER* Core® Technology

PROPERTIES

Couleur	Visuelle	Orange
Densité à 20°C	ASTM D1298	0.926
Viscosité à 40°C (104°F)	ASTM D445	152.0 mm ² /s
Viscosité à 100°C (212°F)	ASTM D445	18.7 mm ² /s
Indice de viscosité	ASTM D2270	140.0
Point éclair	ASTM D92	274.0 °C / 525.0 °F