

8100 X-MAX 0W-40**Gasoline and Diesel engine oil
Synthese-Technologie - Full SAPS****TYPE OF USE**

Synthese-Technologie Hochleistungsmotorenöl für modernste Fahrzeuggenerationen angetrieben von leistungsstarken Benzin- oder Dieselmotoren (ohne DPF) mit Direkteinspritzung. Besonders empfohlen für High-Performance-Motoren z. B. von BMW und Mercedes.

PERFORMANCES

The MERCEDES MB 229.5 standard is more stringent than 229.3 in terms of oil ageing and oil film resistance (extended drain interval: on-board computer), detergent/dispersant power (ACEA B4) and requests fuel economy performance: 1.7 % fuel economy improvement versus a 15W-40 reference.

The specification MB 229.5 applies to all MERCEDES Gasoline engines, including AMG and except SLR, and to all MERCEDES Diesel without DPF engines.

The Porsche A40 standard requires extreme high shear resistance from the lubricant. This specification applies to all PORSCHE engines, except Cayenne V6 and Diesel versions (for these specific engines, use an approved Porsche C30 lubricant such as MOTUL 8100 X-clean+ 5W-30).

The VW 502 00 and 505 00 standards are specially designed for vehicles of the VAG group (VOLKSWAGEN, AUDI, SKODA and SEAT) running on fixed oil drain intervals (15,000 km in Europe), fitted with Diesel engines, without Unit Pump Injector (Volkswagen PD), without Diesel Particulate Filter (DPF), or Gasoline engines.

The FORD WSS-M2C937-A specification requires an extra high oil film resistance for the lubricant to guarantee the viscosity capability over the whole oil drain interval even in severe and extreme conditions (sustained and sport driving,...). This specification applies to all FORD Focus RS 2.5L Turbo Duratec vehicles from MY2008.

MOTUL 8100 X-max 0W-40 meets the performance of the BMW Long Life-01 standard from the BMW Group for BMW, MINI and ROLLS-ROYCE vehicles until the model year 2019 i.e. up to End of 2018 only. For models from 2019 onward requiring an approved BMW LL-01 lubricant, products such as MOTUL 8100 X-cess 5W-30 or MOTUL 8100 X-cess GEN2 5W-40 must be used.

The performance level of FIAT 9.55535-Z2 in 0W-40 requires the lubricant to be both ACEA A3/B4 and 0W-40, in order to

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 -

lubricate perfectly some very recent gasoline engines from FIAT, ALFA-ROMEO, and LANCIA.

MOTUL 8100 X-max 0W-40 meets all these very demanding requirements of performance and durability set by OEMs, as well as the latest level of international standard API.

The API SN standard requires from the lubricant performance an outstanding detergent/dispersant power, a better viscosity increase resistance against deposits, and high lubricating properties such as wear protection and high temperature resistance for better controlled oil consumption and perfect engine protection over the oil drain interval.

The viscosity grade SAE 0W-40 minimizes oil hydrodynamic friction, allowing fuel economy especially when oil is cold. Improves oil flow at start up, faster oil pressure build up, faster rev raisings and faster operating temperature reach.

Environment friendly, this type of oil allows fuel consumption reduction and therefore minimizes greenhouse gases (CO₂) emissions.

Numerous OEMs such as NISSAN, JAGUAR, LAND-ROVER, etc... recommend using a lubricant with 0W-40 viscosity grade and at least API SM for most of their sporty vehicles like for example the NISSAN GT-R, 370Z, 350Z,...

MOTUL 8100 X-max 0W-40 formulation is the perfect balance between fuel economy linked to its viscosity grade and outstanding lubrication performance (high HTHS > 3.5 mPa.s).

RECOMMENDATIONS

Drain interval: refer to manufacturers' recommendations and tune to your own use.

MOTUL 8100 X-max 0W-40 can be mixed with synthetic or mineral oils.

Before use always refer to the owner's manual or handbook of the vehicle.

PROPERTIES

Grade de viscosité	SAE J 300	0W-40
Densité à 20°C	ASTM D1298	0.841
Viscosité à 40°C (104°F)	ASTM D445	76.2 mm ² /s
Viscosité à 100°C (212°F)	ASTM D445	13.5 mm ² /s

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 -



8100 X-MAX 0W-40

**Gasoline and Diesel engine oil
Synthese-Technologie - Full SAPS**

Viscosité HTHS à 150°C (302°F)	ASTM D4741	3.6 mPa.s
Indice de viscosité	ASTM D2270	184.0
Point d'écoulement	ASTM D97	-45.0 °C / -49.0 °F
Cendres sulfatées	ASTM D874	1.10 % masse
TBN	ASTM D2896	10.1 mg KOH/g
Point éclair	ASTM D92	228.0 °C / 442.0 °F



8100 X-MAX 0W-40

Gasoline and Diesel engine oil
Synthese-Technologie - Full SAPS

STANDARDS	
ACEA	A3 / B4
API	SERVICE SN
FORD	WSS-M2C937-A
MERCEDES-BENZ	MB-Approval 229.5
PORSCHE	A40
VW	502 00 505 00
OE PERFORMANCES	
BMW	LL-01 bis Ende Modelljahr 2018
CHRYSLER	MS-12991
FIAT	9.55535-M2, 9.55535-N2, 9.55535-Z2