



MOTUL 8100 ECO-ENERGY 0W-30



**Fuel Economy Gasoline and Diesel lubricant
Synthetic Technology**

TYPE OF USE

Fuel Economy Engine Oil, synthetic technology, specially formulated for recent engines, Diesel or Gasoline, naturally aspirated or turbocharged, indirect or direct injection, requiring use of a low friction and low HTHS (High Temperature High Shear) viscosity oil.

Suitable for all modern engines powered with turbo Diesel or Gasoline engines requiring Fuel Economy lubricants (ACEA A1/B1 or ACEA A5/B5 standards). Compatible for catalytic converters.

This type of oil may be unsuitable for use in some engines. Always refer to the owner manual.

PERFORMANCES

STANDARDS	ACEA A5/B5 API PERFORMANCE SL/CF / SERVICE SP
APPROVALS	BMW LL-01 FE VOLVO VCC 95200377
PERFORMANCES	MERCEDES-BENZ MB-Approval 229.6
RECOMMENDATIONS	HONDA, LAND ROVER, VOLVO

The Volvo Car Corporation – VCC 95200377 specification imposes the engine oil to combine both ACEA A5/B5 and 0W-30 performance in order to perfectly lubricate most of their Naturally Aspirated and Turbocharged Gasoline engines (2.0L, 2.3L, 2.4L, 2.5L, 3.0L, 3.2L and 4.4L) produced from 2004.

Some other OEMs require also for their most recent Gasoline engines (since 2005) an ACEA A5/B5 and 0W-30 lubricant to guarantee the maximum Fuel Economy and durability performance. Examples of MOTUL 8100 Eco-clean 0W-30 possible use for these OEMs: HONDA 1.8L and 2.0L ; and LAND ROVER 3.2L.

The ACEA A5/B5 performance requests from the lubricant a real fuel economy and low emission performance for powerful engines: MOTUL 8100 Eco-nergy 0W-30 has synthetic base stocks and specific friction modifier molecules that provide outstanding oil film resistance, reduce friction in the engine, maintain the oil pressure, and generally decrease operating temperature. MOTUL 8100 Econergy 0W-30 provides high lubricating properties such as wear protection and high temper-

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL Deutschland GmbH - Butzweilerhofallee 3 - 50829 - Köln - +49(0)221/67003-0 - +49(0)221/67003-199 - info@motul.de - http://www.motul.com

[motul.com](http://www.motul.com)



MOTUL 8100 ECO-ENERGY 0W-30



**Fuel Economy Gasoline and Diesel lubricant
Synthetic Technology**

ature resistance for better controlled oil consumption.

Viscosity grade SAE 0W-30 minimizes oil hydrodynamic friction, allowing fuel economy especially when oil is cold. Improves oil flow at start up, faster oil pressure build up, faster rev raisings and faster operating temperature reach.

Environment friendly, this type of oil allows fuel consumption reduction and therefore minimizes greenhouse gases (CO₂) emissions.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.

MOTUL 8100 Eco-nergy 0W-30 can be mixed with synthetic or mineral oils.

Before use always refer to the owner manual or handbook of the vehicle.

PROPERTIES

Viscosity grade	SAE J 300	0W-30
Density at 20°C (68°F)		0.840
	ASTM D445	53.9 mm ² /s
Viscosity at 40°C (104°F)		
	ASTM D445	10.4 mm ² /s
Viscosity at 100°C (212°F)		
HTHS viscosity at 150°C (302°F)	ASTM D4741	3.0 mPa.s
	ASTM D2270	186.0
Viscosity Index		
	ASTM D97	-42.0 °C / -44.0 °F
Pour point		
Sulfated Ash	ASTM D874	
		% weight
		1.09
TBN	ASTM D2896	10.1 mg KOH/g
Flash point	ASTM D92	228.0 °C / 442.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL Deutschland GmbH - Butzweilerhofallee 3 - 50829 - Köln - +49(0)221/67003-0 - +49(0)221/67003-199 - info@motul.de - http://www.motul.com

motul.com