



MOTUL 8100 ECO-CLEAN 0W-30



**Fuel Economy Gasoline & Diesel lubricant
Synthetic Technology**

TYPE OF USE

High performance synthetic technology Fuel Economy Engine Oil specially designed for OEMs requiring a low friction, low HTHS (≥ 2.9 mPa.s) viscosity and "Mid SAPS" oil with reduced content of Sulfated Ash ($\leq 0.8\%$), Phosphorus ($\leq 0.09\%$) and Sulfur ($\leq 0.3\%$). Suitable for the latest generation of Gasoline and Diesel engines, Euro 4, 5 or 6 emission regulation compliant, requiring a "Fuel Economy" lubricant: ACEA C2 standard. Compatible with catalytic converters and Diesel Particulate Filters (DPF).

PERFORMANCES

RECOMMENDATIONS HONDA, SUBARU, SUZUKI, TOYOTA

Synthese-Technologie Fuel Economy engine lubricant specially formulated to ensure optimal lubrication of FORD latest generation Duratorq 1.5L, 1.6L and 2.0L Diesel engines requiring the specification FORD WSS-M2C950-A.

Some modern Diesel engines from JAGUAR and LAND ROVER require engine oil with STJLR.03.5007 specification based on ACEA C2 and 0W-30 profile, in order to protect their after treatment systems while bringing Fuel Economy benefits at the same time.

The FIAT 9.55535-GS1 and FIAT 9.55535-DS1 specifications impose the engine oil to combine both ACEA C2 and SAE 0W-30 performance in order to perfectly lubricate some of the latest generation of Gasoline (FIAT 9.55535-GS-1) and Diesel (FIAT 9.55535-DS-1) engines from Fiat Group (Fiat, Alfa-Romeo, Lancia).

Within the FCA Group (Fiat Chrysler Automobiles), the Chrysler MS-13340 and MS-90047 specifications respectively reflect these FIAT 9.55535-GS1 and DS1 specifications within CHRYSLER.

The HONDA, TOYOTA, SUBARU and SUZUKI recommendations impose the engine oil to combine both ACEA C2 and 0W-30 qualities in order to guarantee the maximum Fuel Economy and durability performance for most of their Gasoline and Diesel engines of latest generation produced since 2006.

Examples of MOTUL 8100 Eco-clean 0W-30 possible use for these OEMs: HONDA 2.2L CDTI and i-DTEC ; TOYOTA 2.0L and 2.2L D4D ; SUBARU 2.0L D ; and SUZUKI SX-4 S-Cross 1.6L DDIS.

Engines compliant with Euro 4, 5 and 6 emission regulation are fitted with sensitive exhaust gas after treatment systems. Indeed, Sulfur and Phosphorus inhibit catalytic converters operation leading to inefficient exhaust gas treatment; and Sulfated Ashes clog DPFs leading to shorten regenerating cycle, quick oil aging, higher fuel consumption and engine power loss.

The ACEA C2 standard requests from the lubricant significant Fuel Economy and Low Emission performance for powerful

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL Deutschland GmbH - Butzweilerhofallee 3 - 50829 - Köln - +49(0)221/67003-0 - +49(0)221/67003-199 - info@motul.de - http://www.motul.com

[motul.com](http://www.motul.com)



MOTUL 8100 ECO-CLEAN 0W-30



**Fuel Economy Gasoline & Diesel lubricant
Synthetic Technology**

engines: MOTUL 8100 Eco-clean 0W-30 has synthetic base stocks and dedicated SAPS levels that generates outstanding oil film resistance, reduces friction in the engine and provides after treatment devices compatibility. MOTUL 8100 Eco-clean 0W-30 brings high lubricating properties such as wear protection and high temperature resistance for better controlled oil consumption.

The viscosity grade SAE 0W-30 minimizes oil hydrodynamic friction, allowing fuel economy especially when oil is cold. Improves oil flow at start up, faster oil pressure build up, faster rev raisings and faster operating temperature reach.

Environment friendly, this type of oil allows fuel consumption reduction and therefore minimizes greenhouse gases (CO₂) emissions.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.

Do not mix with lubricants not ACEA C2 compliant.

Before use always refer to the owner manual or handbook of the vehicle.

PROPERTIES

Viscosity grade	SAE J 300	0W-30
Density at 20°C (68°F)		0.845
	ASTM D445	51.2 mm ² /s
Viscosity at 40°C (104°F)		
	ASTM D445	9.8 mm ² /s
Viscosity at 100°C (212°F)		
HTHS viscosity at 150°C (302°F)	ASTM D4741	2.9 mPa.s
	ASTM D2270	181.0
Viscosity Index		
	ASTM D97	-45.0 °C / -49.0 °F
Pour point		
Sulfated Ash	ASTM D874	
		% weight
		0.79

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.



MOTUL 8100 ECO-CLEAN 0W-30



Fuel Economy Gasoline & Diesel lubricant
Synthetic Technology

TBN	ASTM D2896	8.0 mg KOH/g
Flash point	ASTM D92	222.0 °C / 432.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

06/24

MOTUL Deutschland GmbH - Butzweilerhofallee 3 - 50829 - Köln - +49(0)221/67003-0 - +49(0)221/67003-199 - info@motul.de - http://www.motul.com



MOTUL 8100 ECO-CLEAN 0W-30



Fuel Economy Gasoline & Diesel lubricant
Synthetic Technology

STANDARDS	
ACEA	C2
API	SERVICE SP-RC
BMW	LL-12 FE
FORD	WSS-M2C950-A
ILSAC	GF-6A
OEM PERFORMANCES	
CHRYSLER	MS 13340, MS 90047
FIAT	9.55535-DS1, 9.55535-GS1
MERCEDES-BENZ	MB 227.61, MB-Approval 229.61

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

06/24