



MOTUL 8100 ECO-LITE 0W-20

Fuel Economy Gasoline engine lubricant
100% Synthetic

TYPE OF USE

100% Synthetic "Fuel Economy" engine oil specially designed for recent gasoline engines, naturally aspirated or turbo-charged, indirect or direct injection, designed to use oil with low friction and very low HTHS (High Temperature High Shear) viscosity (≥ 2.6 mPa.s).

Suitable for modern gasoline engines requiring a viscosity grade 20 and fuel economy lubricant (API SQ-RC, API SQ and/or ILSAC GF-7A standards).

Recommended for all GM gasoline engines requiring GM-dexos1™ GEN3 specification: BUICK, CADILLAC, CHEVROLET, GM, GMC, OPEL and VAUXHALL.

Catalytic converter friendly.

This type of oil may be unsuitable for use in some engines. Refer to the owner manual if in doubt.

PERFORMANCES

RECOMMENDATIONS ACURA, HONDA, HYUNDAI, INFINITI, KIA, LEXUS, MAZDA, MITSUBISHI, NISSAN, SUBARU, SUZUKI, TOYOTA

The API SQ standard is fully backward compatible over API SP requirements and all former API standards. The API SQ-RC "Resource Conserving" specification is even more demanding on the energy saving requirements.

API SQ lubricants provide outstanding oxidation resistance, better anti-deposits protection, better engine cleanliness, anti-wear protection and enhanced performance at cold temperature for Fuel Economy savings during the whole oil life span.

Besides being backward compatible, compare to API SP, the API SQ standard provides higher performance and especially adds more protection against LSPI phenomenon for downsized direct injection turbocharged gasoline engines.

Based on the API SQ specification, the ILSAC GF-7A standard for viscosity grade 20 lubricants is even more severe especially on the Fuel Economy benefits performance. The requirements on the low viscosity "Fuel Economy" side of the lubricant, but also extended drain intervals, pistons/rings cleanliness, seals compatibility and reduced content of Phosphorus for after treatment systems compatibility are enhanced. The ILSAC GF-6A specification also ensures perfect engine protection when gasoline containing up to 85% Ethanol is used (E85).

GM dexos1™ standard is suitable for the whole range of GM Gasoline engines from Model Year 2011 onwards requiring an approved dexos1 lubricant (except for service fill in Europe). Specification GM dexos1™ is designed for use with gasoline

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com

10/25

engines and replaces GM-LL-A-025, GM 6094M and GM 4718M. GM dexos1™ is also backward compatible for pre-2011 GM gasoline vehicles.

GM dexos1™ standard combines very stringent requirements from international standards like API, ACEA and ILSAC, together with specific GM requirements to prove Fuel Economy benefits and engine durability.

GM has developed its dexos1™ standard in order for the oils to provide a high thermal stability and insure an outstanding resistance at high temperatures to avoid black sludge and viscosity increase that soot, coming from combustion residues, may create.

Turbocharged gasoline engines with direct injection have a certain risk of sporadic pre-ignition phenomena in the combustion chambers. This type of sporadic abnormal combustion resembles metallic noise from combustion chambers and is sometimes associated with a short power loss. This phenomenon called LSPI for Low Speed Pre-Ignition, or also Rumble, generates very high pressure peaks in the combustion chamber that can lead to piston damages and ultimately to engine destruction. For their latest-generation downsized gasoline engines, which are equipped with direct injection systems and turbochargers, GM has developed the dexos1™ GEN2 and dexos1™ GEN3 standard for engine lubricants in order to guarantee the perfect integrity of these gasoline engines facing the risk of these abnormal combustions.

Likewise, the API SQ standard now fully covers this LSPI requirement in order to perfectly protect direct injection turbocharged gasoline engines.

Some OEMs require for their most recent Gasoline engines an API SP-RC, API SP, API SN, SN-RC, SN Plus and ILSAC GF-6A or GF-5 lubricant to guarantee the maximum performance and durability. The specifications CHRYSLER MS-6395 (GF-4 level), FORD WSS-M2C947-A (GF-5 level), FORD WSS-M2C947-B1 (GF-5, SN-RC and SN Plus levels) and FORD WSS-M2C962-A1 (GF-6, SP-RC and SN Plus levels) reflect these kinds of requirements.

Within the FCA Group (Fiat Chrysler Automobiles), the FIAT specification 9.55535-CR1 mirrors this CHYSLER MS-6395 specification at Fiat.

MOTUL 8100 Eco-lite 0W-20 meets all these very highly demanding requirements of performance and durability set by GM, including in particular for dexos1™ standard, the full compatibility to biofuels use such as LPG (Liquefied Petroleum Gas), CNG (Compressed Natural Gas), and bioethanol (as available at the station), when using ethanol biofuel at a mix ratio of up to 85% (Bioethanol – E85).

Viscosity grade SAE 0W-20 minimizes lubricant hydrodynamic friction, allows fuel economy benefits especially when the oil is cold.

Improves oil flow at start up, faster oil pressure build-up, faster rev raisings and reach operating temperature faster.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.



MOTUL 8100 ECO-LITE 0W-20

Fuel Economy Gasoline engine lubricant
100% Synthetic

Environment friendly, this type of oil allows fuel consumption reduction and therefore minimizes greenhouse gases (CO₂) emissions.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.
MOTUL 8100 Eco-lite 0W-20 can be mixed with synthetic or mineral oils.
Before use always refer to the owner manual of the vehicle.

PROPERTIES

Viscosity grade	SAE J 300	0W-20
Density at 20°C (68°F)	ASTM D1298	0.842
Viscosity at 40°C (104°F)	ASTM D445	45.2 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	8.4 mm ² /s
HTHS viscosity at 150°C (302°F)	ASTM D4741	2.6 mPa.s
Viscosity Index	ASTM D2270	162.0
Pour point	ASTM D97	-42.0 °C / -44.0 °F
Sulfated Ash	ASTM D874	% weight 0.84
TBN	ASTM D2896	8.40 mg KOH/g
Flash point	ASTM D92	223.0 °C / 433.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.



MOTUL 8100 ECO-LITE 0W-20

Fuel Economy Gasoline engine lubricant
100% Synthetic

STANDARDS	
API	SERVICE SQ-RC
ILSAC	GF-7A
OEM PERFORMANCES	
CHRYSLER	MS 6395
FIAT	9.55535-CR1
FORD	WSS-M2C947-A, WSS-M2C947-B1, WSS-M2C962-A1
GENERAL MOTORS	GM dexos1 GEN3

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.