



MOTUL 8100 ECO-LITE 5W-20



**Fuel Economy Petrol engine lubricant
100% Synthetic**

TYPE OF USE

100% Synthetic "Fuel Economy" engine oil specially designed for recent petrol engines, naturally aspirated or turbo-charged, indirect or direct injection, designed to use oil with low friction and very low HTHS (High Temperature High Shear) viscosity (≥ 2.6 mPa.s).

Suitable for modern petrol engines requiring a viscosity grade 20 and fuel economy lubricant (API SQ-RC, API SQ and/or ILSAC GF-7A standards).

Recommended for all GM petrol engines requiring GM-dexos1™ GEN2 specification : BUICK, CADILLAC, CHEVROLET, GM, GMC, OPEL and VAUXHALL.

Catalytic converter friendly.

This type of oil may be unsuitable for use in some engines. Refer to the owner manual if in doubt.

PERFORMANCES

RECOMMENDATIONS ACURA, FIAT, HONDA, HYUNDAI, INFINITI, KIA, LEXUS, MAZDA, MITSUBISHI, NISSAN, SUBARU, SUZUKI, TOYOTA

The API SQ standard is fully backward compatible over API SP requirements and all former API standards. The API SQ-RC "Resource Conserving" specification is even more demanding on the energy saving requirements.

API SQ lubricants provide outstanding oxidation resistance, better anti-deposits protection, better engine cleanliness, anti-wear protection and enhanced performance at cold temperature for Fuel Economy savings during the whole oil life span.

Besides being backward compatible, compare to API SP, the API SQ standard provides higher performance and especially adds protection against LSPI for downsized direct injection turbocharged petrol engines.

Based on the API SP specification, the ILSAC GF-7A standard for viscosity grade 20 lubricants is even more severe especially on the Fuel Economy benefits performance. The requirements on the low viscosity "Fuel Economy" side of the lubricant, but also extended drain intervals, pistons/rings cleanliness, seals compatibility and reduced content of Phosphorus for after treatment systems compatibility are enhanced. The ILSAC GF-7A specification ensures perfect engine protection when petrol containing up to 85% Ethanol is used (E85).

GM dexos1™ standard is suitable for the whole range of GM petrol engines from Model Year 2011 onwards requiring an approved dexos1 lubricant (except for service fill in Europe). Specification GM dexos1™ is designed for use with petrol

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com

09/25



MOTUL 8100 ECO-LITE 5W-20



**Fuel Economy Petrol engine lubricant
100% Synthetic**

engines and replaces GM-LL-A-025, GM 6094M and GM 4718M. GM dexos1™ is also backward compatible for pre-2011 GM petrol vehicles.

GM dexos1™ standard combines very stringent requirements from international standards like API, ACEA and ILSAC, together with specific GM requirements to prove Fuel Economy benefits and engine durability.

GM has developed its dexos1™ standard in order for the oils to provide a high thermal stability and insure an outstanding resistance at high temperatures to avoid black sludge and viscosity increase that soot, coming from combustion residues, may create.

Turbocharged petrol engines with direct injection have a certain risk of sporadic pre-ignition phenomena in the combustion chambers. This type of sporadic abnormal combustion resembles metallic noise from combustion chambers and is sometimes associated with a short power loss. This phenomenon called LSPI for Low Speed Pre-Ignition, or also Rumble, generates very high pressure peaks in the combustion chamber that can lead to piston damages and ultimately to engine destruction. For their latest-generation downsized petrol engines, which are equipped with direct injection systems and turbochargers, GM has developed the dexos1™ GEN2 standard for engine lubricants in order to guarantee the perfect integrity of these petrol engines facing the risk of these abnormal combustions.

Likewise, the API SQ standard now fully covers this LSPI requirement in order to perfectly protect direct injection turbo-charged petrol engines.

Some OEMs require for their most recent petrol engines an API SP-RC, API SP, API SN, SN-RC, SN Plus and ILSAC GF-6A or GF-5 lubricant to guarantee the maximum performance and durability. The specifications CHRYSLER MS-6395 (GF-4 level), FORD WSS-M2C930-A (GF-4 level), FORD WSS-M2C945-A (GF-5 level), FORD WSS-M2C945-B1 (GF-5, SN-RC and SN Plus levels) and FORD WSS-M2C960-A1 (GF-6, SP-RC and SN Plus levels) reflect these kinds of requirements.

Within the FCA Group (Fiat Chrysler Automobiles), the FIAT specification 9.55535-CR1 mirrors this CHRYSLER MS-6395 specification at Fiat.

MOTUL 8100 Eco-lite 5W-20 meets all these very highly demanding requirements of performance and durability set by GM, including in particular for dexos1™ standard, the full compatibility to biofuels use such as LPG (Liquefied Petroleum Gas), CNG (Compressed Natural Gas), and bioethanol (as available at the station), when using ethanol biofuel at a mix ratio of up to 85% (Bioethanol – E85).

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com

09/25



MOTUL 8100 ECO-LITE 5W-20



**Fuel Economy Petrol engine lubricant
100% Synthetic**

Viscosity grade SAE 5W-20 minimizes lubricant hydrodynamic friction, allows fuel economy benefits especially when the oil is cold.

Improves oil flow at start up, faster oil pressure build-up, faster rev raisings and reach operating temperature faster.

Environment friendly, this type of oil allows fuel consumption reduction and therefore minimizes greenhouse gases (CO₂) emissions.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.

MOTUL 8100 Eco-lite 5W-20 can be mixed with synthetic or mineral oils.

Before use always refer to the owner manual of the vehicle.

PROPERTIES

Viscosity grade	SAE J 300	5W-20
Density at 20°C (68°F)	ASTM D1298	0.847
Viscosity at 40°C (104°F)	ASTM D445	44.7 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	8.5 mm ² /s
HTHS viscosity at 150°C (302°F)	ASTM D4741	2.6 mPa.s
Viscosity Index	ASTM D2270	170.0
Pour point	ASTM D97	-42.0 °C / -44.0 °F
Sulfated Ash	ASTM D874	% weight 0.85
TBN	ASTM D2896	8.5 mg KOH/g
Flash point	ASTM D92	236.0 °C / 433.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com

09/25



MOTUL 8100 ECO-LITE 5W-20



Fuel Economy Petrol engine lubricant
100% Synthetic

STANDARDS	
API	SERVICE SQ-RC
ILSAC	GF-7A
OEM PERFORMANCES	
CHRYSLER	MS 6395
FIAT	9.55535-CR1
FORD	WSS-M2C930-A, WSS-M2C945-A, WSS-M2C945-B1, WSS-M2C960-A1
GENERAL MOTORS	GM dexos1 GEN2

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com