



MOTUL 8100 POWER 0W-20

High Performance engine oil - Gasoline & Diesel
Ester Core®

TYPE OF USE

High Performance - ESTER engine oil inspired by motorsport and specifically designed for gasoline or diesel engines, tuned or high performance, naturally aspirated or turbocharged, indirect or direct injection, operating in a wide range of speeds and temperatures in the harshest road or racing conditions.

Suitable for gasoline and diesel engines that require an engine oil in the viscosity grade SAE 0W-20 and API SP.

The exclusive formula of MOTUL 8100 POWER 0W-20 is compatible with biofuels (especially with ethanol E85) and exhaust aftertreatment systems. It also protects downsized engines from uncontrolled pre-ignition at low speed under high load (LSPI), and the low viscosity optimizes engine response and maximum power.

Very good compatibility with catalytic converters.

Suitable for all types of gasoline fuels, leaded or unleaded, ethanol, LPG, diesel and biofuels.

This type of oil may be unsuitable for use in some engines. Always read the operating instructions before use.

PERFORMANCES

STANDARDS

API PERFORMANCE SP

ESTER Technology: 100% Synthetic formula derived from competition and based on Ester ensuring outstanding oil film resistance at very high temperatures for maximum engine power and torque, as well as maximum wear protection. Stable oil pressure whatever the conditions of use, road or racing.

Turbocharged gasoline engines with direct injection have a certain risk of sporadic pre-ignition phenomena in the combustion chambers. This type of sporadic abnormal combustion resembles metallic noise from combustion chambers and is sometimes associated with a short power loss. This phenomenon called LSPI for Low Speed Pre-Ignition, or also Rumble, generates very high pressure peaks in the combustion chamber that can lead to piston damages and ultimately to engine destruction.

For their latest-generation downsized gasoline engines, which are equipped with direct injection systems and turbochargers, API has developed the API SP standard for engine lubricants in order to guarantee the perfect integrity of these gasoline engines facing the risk of these abnormal combustions.

The API SP standard is fully backward compatible over API SN requirements and all former API standards. API SP lubri-

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL Deutschland GmbH - Butzweilerhofallee 3 - 50829 - Köln - +49(0)221/67003-0 - +49(0)221/67003-199 - info@motul.de - http://www.motul.com

motul.com



MOTUL 8100 POWER 0W-20

**High Performance engine oil - Gasoline & Diesel
Ester Core®**

cants provide outstanding oxidation resistance, better anti-deposits protection, better engine cleanliness, anti-wear protection and enhanced performance at cold temperature for Fuel Economy savings during the whole oil life span. Besides being backward compatible, compare to API SN and API SN Plus, the API SP standard provides higher performance and especially adds more protection against LSPI phenomenon for downsized direct injection turbocharged gasoline engines.

MOTUL 8100 POWER 0W-20 meets all these very highly demanding requirements of performance and durability, including in particular for API SP standard, the full compatibility to biofuels use such as LPG (Liquefied Petroleum Gas), CNG (Compressed Natural Gas), and Bioethanol (as available at the station), when using Ethanol Biofuel at a mix ratio of up to 85% (Bioethanol – E85).

Viscosity grade SAE 0W-20 minimizes lubricant hydrodynamic friction, allows fuel economy benefits especially when the oil is cold. MOTUL 8100 POWER 0W-20 allows faster oil flow at start up, faster oil pressure build-up, sharper engine revs and faster engine warm-up.

Environment friendly, this type of oil allows fuel consumption reduction and therefore minimizes greenhouse gases (CO₂) emissions.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and to be tuned to your own use.

MOTUL 8100 POWER 0W-20 can be mixed with synthetic or mineral oils.

Before use always refer to the owner manual of the vehicle.

PROPERTIES

Viscosity grade	SAE J 300	0W-20
Density at 20°C (68°F)		0.840
	ASTM D445	48.1 mm ² /s
Viscosity at 40°C (104°F)		
	ASTM D445	8.7 mm ² /s
Viscosity at 100°C (212°F)		
HTHS viscosity at 150°C (302°F)	ASTM D4741	2.7 mPa.s

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.



MOTUL 8100 POWER 0W-20

High Performance engine oil - Gasoline & Diesel
Ester Core®

Viscosity Index	ASTM D2270	161.0
Pour point	ASTM D97	-48.0 °C / -54.0 °F
Sulfated Ash	ASTM D874	% weight
		0.79
TBN	ASTM D2896	8.5 mg KOH/g
Flash point	ASTM D92	238.0 °C / 460.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

06/24

MOTUL Deutschland GmbH - Butzweilerhofallee 3 - 50829 - Köln - +49(0)221/67003-0 - +49(0)221/67003-199 - info@motul.de - http://www.motul.com