



## 8100 XPOWER 10W60 DE

**High Performance Gasoline Engine Oil  
Synthese-Technologie**

### TYPE OF USE

Synthese-Technologie lubricant specially designed for high performance cars with naturally aspirated, compressed or turbocharged engines.

Especially recommended for ALFA ROMEO GT Series / AUDI R8 5.2L GT (CMPA) / ASTON MARTIN / BMW M Series / FERRARI V12 / JAGUAR / LANCIA / LOTUS / MASERATI / TVR ...

Suitable for all kind of operating conditions and for all type of fuels: Gasoline leaded or unleaded, Ethanol, LPG, Diesel and biofuels.

Compatible for catalytic converters.

### PERFORMANCES

STANDARDS	ACEA A3/B4 API SERVICE SP
PERFORMANCES	FIAT 9.55535-H3

The ACEA A3 / B4 and API SP standards require from the lubricant an outstanding detergent/dispersant power, a better viscosity increase resistance against deposits, and high lubricating properties such as wear protection and high temperature resistance for better controlled oil consumption and perfect engine protection over the oil drain interval.

Besides being backward compatible, compare to API SN and API SN Plus, the API SP standard provides higher performance and especially adds protection against LSPI for downsized direct injection turbocharged gasoline engines.

The FIAT 9.55535-H3 performance level imposes the engine lubricant to combine both ACEA A3 / B4 standard and 10W-60 viscosity grade in order to perfectly lubricate some high performance engines of FIAT, ALFA-ROMEO and LANCIA, especially V6 Gasoline.

MOTUL 8100 X-POWER 10W-60 provides longer lasting protection in lower or higher mileage engines for a longer lifetime of the vehicle.

Extra oil film thickness reduces oil burn off in the combustion chamber and helps preventing oil leaks.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

[motul.com](http://motul.com)



## 8100 XPOWER 10W60 DE

High Performance Gasoline Engine Oil  
Synthese-Technologie

The outstanding fluid strength provides high engine protection and stable oil pressure over the drain interval.

### RECOMMENDATIONS

Drain interval: Refer to manufacturers' recommendations and tune to your own use.

MOTUL 8100 X-POWER 10W-60 can be mixed with synthetic or mineral oils.

Can be used on Diesel engines requiring performances.

Before use always refer to the owner manual or handbook of the vehicle.

### PROPERTIES

Viscosity grade	SAE J 300	10W-60
Density at 20°C (68°F)	ASTM D1298	0.850
Viscosity at 40°C (104°F)	ASTM D445	154.9 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	23.6 mm <sup>2</sup> /s
HTHS viscosity at 150°C (302°F)	ASTM D4741	5.8 mPa.s
Viscosity Index	ASTM D2270	183.0
Pour point	ASTM D97	-33.0 °C / -27.0 °F
Sulfated Ash	ASTM D874	% weight 1.07
TBN	ASTM D2896	12.5 mg KOH/g
Flash point	ASTM D92	228.0 °C / 442.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com