



# GP POWER 4T 10W40

**Lubricant for 4 Stroke motorcycle engine  
SAE 10W-40**

## **TYPE OF USE**

Street & road bikes, trails, off-road bikes fitted with 4 stroke engines, integrated gearbox or not, wet or dry clutch, engines with or without catalytic converters.

Other users: Scooters, ATV, Mopeds...

## **PERFORMANCES**

STANDARDS	API SL
PERFORMANCES	JASO MA2

MOTUL GP POWER 4T 10W40 is specially formulated to provide excellent protection for engine & gearbox. It has high detergent and dispersive properties to provide excellent engine cleanliness and sludge control. The unique additives minimize wear and increase engine and gear life time.

JASO MA2 ensures the perfect clutch lock up at start-up, acceleration and full speed, as well as easy gear shifting.

## **RECOMMENDATIONS**

Drain interval: according to manufacturers' recommendations and to be adjusted according to the using condition. Can be mixed with synthetic or mineral lubricants.

## **PROPERTIES**

Viscosity grade	SAE J 300	<b>10W-40</b>
Density at 20°C (68°F)	ASTM D1298	0.860
Viscosity at 40°C (104°F)	ASTM D445	103.9 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	14.9 mm²/s
Viscosity Index	ASTM D2270	149
Pour point	ASTM D97	-33°C
Flash point	ASTM D92	229°C
TBN	ASTM D2896	5.5 mg KOH/g