



GP MATIC 4T 10W40

**Lubricant for 4 Stroke scooters engine
SAE 10W-40**

TYPE OF USE

All 4 stroke scooter engines for which manufacturers recommend JASO MB oils.
Suitable for all types of gasoline fuels, leaded or unleaded, biofuels.

PERFORMANCES

STANDARDS	API SL
SPECIFICATIONS	JASO MB

MOTUL GP MATIC 4T 10W40 is specially formulated to provide excellent protection for engine. It provides good sludge control and anti-oxidation properties to minimize premature oil ageing. The high temperature resistance property is particularly suitable for city use: full load during long periods and stop and go use with difficult cooling.

JASO MB lubricant ensures optimal scooter performance and fuel economy.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and to be adjusted according to the using condition. Can be mixed with synthetic or mineral oils.

MOTUL GP MATIC 4T 10W40 should not be used on system that requires JASO MA specification.

PROPERTIES

Viscosity grade	SAE J 300	10W-40
Density at 20°C (68°F)	ASTM D1298	0.860
Viscosity at 40°C (104°F)	ASTM D445	101.5 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	14.8 mm²/s
Viscosity Index	ASTM D2270	152
Pour point	ASTM D97	-33°C
Flash point	ASTM D92	230°C
TBN	ASTM D2896	5.7 mg KOH/g