



## ATF 236.14 DE

**Automatic Transmission Fluid for Mercedes Passenger Car  
Automatic Transmission  
Synthese-Technologie**

### TYPE OF USE

High performance Synthese-Technologie lubricant specially engineered for Mercedes RWD (Rear Wheel Drive) and 4x4 AWD (All Wheel Drive) passenger cars, SUV's and light duty utility vehicles automatic transmissions where MB-Approval 236.14 specification is required.

Especially recommended for use in all Mercedes vehicles fitted with the 7 speed RWD automatic transmissions (NAG2) and all AMG models, as well as Mercedes 5 speed automatic transmissions with regulated torque converter lockup clutch, where MB-Approval 236.14 specification is required.

Before use always refer to the owner manual of the vehicle.

### PERFORMANCES

APPROVALS                      MERCEDES-BENZ MB-Approval 236.14

PERFORMANCES                MERCEDES-BENZ A 001 989 45 03, MERCEDES-BENZ A 001 989 68 03

MOTUL ATF 236.14 is a Synthese-Technologie high technology synthetic lubricant featuring outstanding performance with regards to conventional DEXRON and MERCON standards requirements.

MOTUL ATF 236.14 exclusive and dedicated formula:

- Protects the numerous, compact and heavily loaded gears thanks to advance anti-wear properties.
- Extends life time duration, high shear stability at hot temperature and oxidation resistance.
- Allows fuel economy for cars fitted with automatic gearboxes by reducing epicyclical gears friction.
- Improves automatic gearboxes reaction at cold temperature.
- Provides anti-shudder performance and then avoids vibrations on engine fly wheel.
- Gives superior automatic transmission response: smooth shift feel and minimizing shift time lag.
- Anti-wear, anti-corrosion, anti-foam.



## ATF 236.14 DE

Automatic Transmission Fluid for Mercedes Passenger Car  
Automatic Transmission  
Synthese-Technologie

### RECOMMENDATIONS

Can be mixed with similar lubricants.

Oil change: according to manufacturer's recommendations and adapt according to your own use.

**Before use always refer to the owner manual of the vehicle.**

### PROPERTIES

Color	Visual	Red
Density at 20°C (68°F)	ASTM D1298	0.850
Viscosity at 40°C (104°F)	ASTM D445	29.6 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	6.6 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	192.0
Pour point	ASTM D97	-54.0 °C / -65.0 °F
Flash point	ASTM D92	210.0 °C / 410.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br\>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com