



## MOTUL ATF VI

**Low viscosity fluid for automatic transmission with slip lockup clutch**  
**Transfer case and Power steering**  
**100% Synthetic**

### TYPE OF USE

100% Synthetic High performance low viscosity lubricant specially engineered for modern automatic transmission (manual mode, sequential mode, electronically controlled ...) with or without slip lockup clutch requiring a DEXRON VI fluid. Particularly recommended for use in automatic gearboxes, transfer case and power steering systems of American car makers GM, FORD, CHRYSLER,... Asian car makers HONDA, HYUNDAI, KIA, ISUZU, MERCEDES, MITSUBISHI, NISSAN, TOYOTA,... or European car makers FORD, OPEL, ...

Also suitable for use in older automatic gearboxes, torque converters, power steering, mechanical and hydraulic systems where DEXRON III H or DEXRON II D fluids are required.

Before use always refer to the owner manual or handbook of the vehicle.

### PERFORMANCES

MOTUL ATF VI is a 100% Synthetic high tech lubricant featuring outstanding low viscosity performance with regards to DEXRON III and MERCON standards requirements.

Thanks to its exclusive and dedicated formula, MOTUL ATF VI:

- Allows Fuel Economy for cars fitted with automatic gearboxes by reducing friction.
- Improves automatic gearboxes reaction at cold temperature.
- Gives superior automatic transmission response: smooth shift feel and minimizing shift time lag.
- Provides anti-shudder performance to avoid vibrations on engine fly wheel.
- Protects gears that are more and more numerous, compact and heavily loaded.
- Extends life time duration, better shear stability at hot temperature and oxidation resistance.
- Anti-wear, anti-corrosion, anti-foam.

### RECOMMENDATIONS

Can be mixed only with similar lubricants.

Oil change: according to manufacturer's recommendations and adapt according to your own use.

Before use always refer to the owner manual or handbook of the vehicle.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com



## MOTUL ATF VI

**Low viscosity fluid for automatic transmission with slip lockup clutch**  
**Transfer case and Power steering**  
**100% Synthetic**

### PROPERTIES

Color	Visual	Red
Density at 20°C (68°F)	ASTM D1298	0.843
Viscosity at 40°C (104°F)	ASTM D445	30.5 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	6.1 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	152.0
Flash point	ASTM D92	217.0 °C / 423.0 °F

**Low viscosity fluid for automatic transmission with slip lockup clutch**  
**Transfer case and Power steering**  
**100% Synthetic**

OE PERFORMANCES	
<b>ACURA</b>	##08200-9008A, ##08200-9009A, ##08266-99964, #atf, 08200-9008A, 08200-9009A, 08200-9016A, 08266-99964, ATF DW-1 (except CVTs), ATF Z1 (except CVTs)
<b>ALLISON TRANSMISSION</b>	C-4
<b>AUDI</b>	G 052 533, G 053 001, G 053 001 A2, G 055 005, G 055 162, G 055 540, G 060 162, G 060 540 A2
<b>BENTLEY</b>	PY112995PA
<b>BMW</b>	##83220142516, ##83222152426, 83 22 0 142 516, 83 22 0 397 114, 83 22 0 403 248, 83 22 0 403 249, 83 22 0 432 807, 83 22 2 152 426, 83 22 2 163 514, 83 22 2 289 720, 83 22 2 305 396 (ATF2), 83 22 2 305 397, 83 22 2 355 599, 83 22 2 355 601, 83 22 2 413 477 (ATF7), 83 22 9 400 275, 83 22 9 407 738, 83 22 9 407 858, 83 22 9 407 859, ATF 3+, ATF6, L12108
<b>BRILLIANCE</b>	ATF PTF-1
<b>CHRYSLER</b>	##68157995AA, ##68157995AB, ##68218057CA, ##68218058CA, ##68218054CA, ##68218925AA, ##68171869AA, 68043742AB, 68157995AA, 68157995AB, 68171866AA, 68171869AA, 68218054CA, 68218057CA, 68218058CA, 68218925AA, ATF+3, ATF+4, DEXRON®-VI Automatic Transmission Fluid, DEXRON VI Automatic Transmission Fluid, MS 90030-A5, MS 9602, SP IV Automatic Transmission Fluid
<b>CITROËN</b>	05127382, 68043742AA, 68818925AA/AB, 8 & 9 Speed ATF, AW-1, AW-2, RP 9734 R7 for EAT6 transmissions
<b>DAIMLER</b>	##68157995AA, ##68157995AB, ##68218057CA, ##68218058CA, ##68218054CA, ##68218925AA, ##68171869AA, 68043742AB, 68157995AA, 68157995AB, 68171866AA, 68171869AA, 68218054CA, 68218057CA, 68218058CA, 68218925AA, ATF+3, ATF+4, DEXRON®-VI Automatic Transmission Fluid, DEXRON VI Automatic Transmission Fluid, MS 9602, SP IV Automatic Transmission Fluid
<b>DS (CAPSA)</b>	05127382, 68043742AA, 68818925AA/AB, 8 & 9 Speed ATF, AW-1, AW-2, RP 9734 R7 for EAT6 transmissions
<b>FIAT</b>	9.55550-AV5 for ZF automatic gearbox with 8 and 9 speed
<b>FORD</b>	MERCON LV, MERCON ULV, WSS-M2C922-A1, XT-10-QLVC, XT-6-QSP (SP)
<b>GENERAL MOTORS</b>	##9986153, ##88861003, ##88861004, ##9986333, ##GMW16444, 19256039, 88861003, 88861004, 88863400, 88863401, 9986153, 9986333, AW-1, Dex HP, GM 1940184, GM 93165414, GM DEXRON HP ATF, GM DEXRON II D, GM DEXRON III H, GM DEXRON ULV ATF, GM DEXRON VI, GMW16444, GMW16974, WS
<b>HONDA</b>	##082000-9001, ##08266-9904, ##08266-99907, 082000-9001, 08200-9005, 08200-9008, 08200-9016-A, 08200-9017, 08266-9904, 08266-99907, ATF-11, ATF DW-1 (except CVTs), ATF-TYPE 3.1, ATF Z1 (except CVTs), B2618-OLE-025, Type 3.0

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

**Low viscosity fluid for automatic transmission with slip lockup clutch**  
**Transfer case and Power steering**  
**100% Synthetic**

<b>HYUNDAI</b>	##040000C90SG, ##00232-1904/04500-00115, 00232-1904, 040000C90SG, 04500-00115, NWS-9638, SP4-M1, SPH-IV, SP-IV, SP-IV M, SP-IV-RR, WS
<b>INFINITI</b>	MATIC D, MATIC J, MATIC K, MATIC S
<b>ISUZU</b>	Besco ATF III, SCS, WSI
<b>JAGUAR LAND ROVER</b>	##02JDE 26444, 02JDE 26444, Jaguar Fluid 8432
<b>KIA</b>	NWS-9638, SP4-M1, SPH-IV, SP-IV, SP-IV M, SP-IV-RR, WS
<b>LAND ROVER</b>	LR023288, LR023289, TYK500050
<b>LEXUS</b>	##00289-ATFWS, ##08886-02303, ##08886-02305, ##08886-80803, 00289-ATFWS, 08886-02303, 08886-02305, 08886-80803, ATF Type T-IV, ATF WS, JWS 3324, NWS 9638
<b>MASERATI</b>	##231603, 231603, M-1375.4
<b>MAZDA</b>	##0000-77-122E-01, 0000-77-122E-01, ATF FZ, MERCON LV
<b>MERCEDES-BENZ</b>	A 001 989 45 03, A 001 989 68 03, A 001 989 77 03, A 001 989 78 03, MB 236.12, MB 236.14, MB 236.15 (except FE benefits), MB 236.16 (Except FE benefits), MB 236.17 (Except FE benefits), MB 236.41, P/N 0029890603
<b>MINI</b>	BMW 83 22 2 413 477 (ATF7)
<b>MITSUBISHI</b>	4030401, ATF-J3, ATF-MA1, ATF SPH-IV, ATF SP-IV, Diamond ATF SP II, Diamond Queen ATF-PA, MZ320762, MZ320775, SP III
<b>NISSAN</b>	999MP-MPT10P, 999MP-MTS00P, KLE24-00002, MATIC D, MATIC J, MATIC K, MATIC P, MATIC S, MATIC W
<b>PEUGEOT</b>	05127382, 68043742AA, 68818925AA/AB, 8 & 9 Speed ATF, AW-1, AW-2, RP 9734 R7 for EAT6 transmissions
<b>PORSCHE</b>	##00004330400, 000 043 304 00
<b>SAAB</b>	93 165 147
<b>SSANGYONG</b>	DSIH 5M-66 Material Specification Rev 3
<b>SUBARU</b>	ATF-WS
<b>SUZUKI</b>	MATIC S
<b>TOYOTA</b>	##00289-ATFWS, ##08886-02303, ##08886-02305, ##08886-80803, 00289-ATFWS, 08886-02303, 08886-02305, 08886-80803, ATF FZ, ATF Type T-IV, ATF WS, JWS 3324, NWS 9638
<b>VOLVO</b>	31 256 774, 31 256 775
<b>VW</b>	#g 05, #g 052 025, G 052 533, G 053 001, G 055 005, G 055 162, G 055 540, G 060 162, G 060 540 A2
<b>ZF</b>	AA01 500 001, Lifeguard 6, Lifeguard 6 Plus, Lifeguard 8, Lifeguard 9, M-1375.4, M-1375.5, M-1375.6, S671 090 255, S671 090 281, S671 090 312, TE-ML 11
<b>PRODUCTS</b>	
<b>AISIN</b>	ATF-0WS (except CVTs), AW-1, AW-2
<b>AML</b>	##4G4319A509/AA/S, 4G4319A509 / AA / S

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



## MOTUL ATF VI

**Low viscosity fluid for automatic transmission with slip lockup clutch**  
**Transfer case and Power steering**  
**100% Synthetic**

<b>FUCHS</b>	ATF 3292, ATF 4400, ATF 6000 SL
<b>JALOS</b>	Class 1A-LV, M315
<b>JATCO</b>	1A
<b>MOPAR PARTS</b>	68218925AA
<b>PENTOSIN</b>	#ffl
<b>PETRONAS LUBRICANTS</b>	Tutela Transmission AS8
<b>PSA Groupe</b>	#lds, AW-1, RP 9734 R7 for EAT6 transmissions
<b>SHELL</b>	#m, #13, L-12108, M-1375.4, M-1375.5, M-1375.6
<b>ZF</b>	##S671090255, ##S671090281, ##S671090312, AA01 500 001, Lifeguard 6, Lifeguard 6 Plus, Lifeguard 8, Lifeguard 9, M-1375.4, M-1375.5, M-1375.6, S671 090 255, S671 090 281, S671 090 312, TE-ML 11

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

