

ATV-UTV 4T 10W-40

4T-Motorenöl für ATV, UTV
4T-Motorenöl für ATV, UTV
Mineral

TYPE OF USE

All ATV – All Terrain Vehicle, UTV – Utility Terrain/Task Vehicle, quads...fitted with 4 stroke engines, integrated gearbox or not, wet or dry clutch, engines meeting Euro 2, 3, 4 or 5 emission regulation, fitted with exhaust gas after treatment systems: catalytic converters, air injection into exhaust pipe...

ATV-UTV, quads used for leisure and recreation.

Suitable for all type of gasoline fuels, leaded or unleaded, with or without Ethanol, biofuels.

PERFORMANCES

STANDARDS API SL / SJ

PERFORMANCES JALOS MA2 under N° M033MOT176

Engine oil reinforced with specific additives which provide high protection and oil film resistance.

High lubricating properties which decrease friction and wear and increase engine lifetime.

The JASO MA2 approval guarantees the efficient high friction level to secure the clutch engagement during the three riding modes: Starting, Acceleration and Constant Speed.

The SAE 10W-40 viscosity grade corresponds to the most recent manufacturers' recommendations.

Low volatility for reduced oil consumption.

High detergent and dispersive properties.

Anti-oxidation, Anti-corrosion, Anti-foam.

RECOMMENDATIONS

Oil change: according to manufacturers' requirements and to be adjusted according to particular use.

Can be mixed with synthetic or mineral lubricants.



ATV-UTV 4T 10W-40

4T-Motorenöl für ATV, UTV
4T-Motorenöl für ATV, UTV
Mineral

PROPERTIES

Viscosity grade	SAE J 300	10W-40
Density at 20°C (68°F)	ASTM D1298	0.864
Viscosity at 40°C (104°F)	ASTM D445	100.1 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.9 mm ² /s
Viscosity Index	ASTM D2270	156.0
Pour point	ASTM D97	-30.0 °C / -22.0 °F
TBN	ASTM D2896	6.4 mg KOH/g
Flash point	ASTM D92	224.0 °C / 435.0 °F