



MOTUL ATV UTV EXPERT 10W-40 4T

Lubricant for 4 Stroke ATV-UTV engines
Technosynthese® - Ester

TYPE OF USE

ATV – All Terrain Vehicle, UTV – Utility Terrain/Task Vehicle, quads... fitted with 4 Stroke engines, integrated gearbox or not, wet or dry clutch, engines meeting Euro 2, 3, 4 or 5 emission regulation, fitted with exhaust gas after treatment systems: catalytic converters, air injection into exhaust pipe...

ATV-UTV, quads used for leisure and recreation.

Suitable for all type of gasoline fuels, leaded or unleaded, with or without Ethanol, biofuels.

PERFORMANCES

STANDARDS

API SM/SL/SJ

JASO MA2 - M033MOT175

Synthetic engine oil Technosynthese®, reinforced with Ester base stocks which provide outstanding protection and oil film resistance.

Synthetic formula reinforced with anti-wear additives and improved shear resistance for improved oil film resistance at high temperatures.

The JASO MA2 approval guarantees the efficient high friction level to secure the clutch engagement during the three riding modes: Starting, Acceleration and Constant Speed.

Optimized Phosphorus and Sulfur contents for better operating conditions of catalytic converters required to meet latest emission regulation.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral lubricants.



MOTUL ATV UTV EXPERT 10W-40 4T

Lubricant for 4 Stroke ATV-UTV engines
Technosynthese® - Ester

PROPERTIES

Viscosity grade	SAE J 300	10W-40
Density at 20°C (68°F)	ASTM D1298	0.865
Viscosity at 40°C (104°F)	ASTM D445	88.7 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	13.7 mm ² /s
Viscosity Index	ASTM D2270	159.0
Pour point	ASTM D97	-32.0 °C / -26.0 °F
TBN	ASTM D2896	7.5 mg KOH/g
Flash point	ASTM D92	224.0 °C / 435.0 °F