



## ATV POWER 4T 5W-40

**High performance lubricant for ATVs**  
**100% Synthetic - Ester**

### TYPE OF USE

ATV - All-Terrain Vehicles, quads... sporty or urban, fitted with 4 Stroke engines, integrated gearbox or not, wet or dry clutch, engines meeting Euro 2, 3, 4 or 5 emission regulation, fitted with exhaust gas after treatment systems: catalytic converters, air injection into exhaust pipe...

ATVs, quads... used for leisure and recreation.

Suitable for all type of gasoline fuels, leaded or unleaded, with or without Ethanol, biofuels.

### PERFORMANCES

STANDARDS                      API SN / SM / SL / SJ

PERFORMANCES                JALOS MA2 under N° M033MOT173

100% Synthetic - Ester lubricant for improved oil film resistance at high temperatures.

Formula reinforced with Ester and anti-wear additives for improved oil film shear resistance and for increased gear protection and life time duration.

The JASO MA2 approval guarantees the efficient high friction level to secure the clutch engagement during the three riding modes: Starting, Acceleration and Constant Speed.

Optimized Phosphorus and Sulfur contents for better operating conditions of catalytic converters required to meet latest emission regulations.

### RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral lubricants.



## ATV POWER 4T 5W-40

High performance lubricant for ATVs  
100% Synthetic - Ester

### PROPERTIES

Color	Visual	Red
Viscosity grade	SAE J 300	5W-40
Density at 20°C (68°F)	ASTM D1298	0.855
Viscosity at 40°C (104°F)	ASTM D445	79.2 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	13.6 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	172.0
Pour point	ASTM D97	-35.0 °C / -31.0 °F
TBN	ASTM D2896	8.3 mg KOH/g
Flash point	ASTM D92	224.0 °C / 435.0 °F