

CADREX DR 40 SC

Deformation

DESCRIPTION

CADREX DR 40 SC is a chlorine-free, neat oil designed for drawing, bending, reshaping and fine blanking on all ferrous and non-ferrous metals, under low-duty conditions.

APPLICATIONS

For all parts arriving on assembly lines or elements used to make sub-assemblies (sheet steel, bare or coated beforehand with zinc or zinc alloys, sheet aluminum, etc.). Ready to use, it can be used by spraying, brushing or dipping.

ADVANTAGES

- Does not yellow under an HPRL lamp.
- If it is not rinsed off, CADREX DR 40 SC provides temporary protection from all subsequent corrosion, for treated metals.
- Easy to clean before painting application.
- Can protect against corrosion for 1 to 2 months under shelter.

TECHNICAL INFORMATION

NAME	UNITS	METHOD	CADREX DR 40 SC
Color	-	ASTM D1500	Brown
Aspect	-		Light
Density at 20°C (68°F)	-	ISO 12.185	0.930
Viscosity at 40°C (104°F)	mm ² /s	ASTM D445	40.0
Flash point	°C	ASTM D92	>155
Pour point	°C	ASTM D97	-30.0
Copper Strip Corrosion	-	NTF M 07105	1a
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.

Approved by RENAULT, **CADREX DR 40 SC** can be recommended for all subcontractors working for the automotive industry. For severe or deep stamping, use our **CADREX DR 100 SC** and **CADREX DR 220 SC** products respectively.

Specification sheet N°: E2-43-344-R

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.