



DOT 5.1 Brake Fluid

Long life 100% Synthetic Brake Fluid

For hydraulic actuated brake and clutch systems

DOT 5.1 NON SILICONE BASE

TYPE OF USE

For all types of hydraulically actuated brake and clutch systems requiring fluids meeting DOT 3, DOT 4, or DOT 5.1 specifications as per manufacturers' recommendations.

Fluidity specially designed for anti-locking brake systems (ABS) and other electronic stability programs (ESP, ASR,...)

PERFORMANCES

STANDARDS

FMVSS No. 116 DOT 5.1 NON SILICONE BASE
SAE J 1705
ISO 4925 Class 5.1
JIS K2233 Class 5

Long life fluid:

MOTUL DOT 5.1 high wet boiling point (188°C / 370°F) is superior than the requirements of the standards DOT 3 (140°C / 284°F), DOT 4 (155°C / 311°F) and DOT 5.1 (180°C / 356°F), and therefore enables longer use of this product.

Indeed, DOT 3, DOT 4 or DOT 5.1 brake fluids have the property of absorbing moisture from the air, which reduces their boiling points and therefore braking safety.

The wet boiling point is measured after moistening the product with 3% water in order to be representative of the state of the fluid after 1 year of use.

Perfectly neutral with seals used in braking systems. Anti-corrosion.

Specially designed for anti-locking brake systems (ABS):

The viscosity at cold temperature (830 mm²/s at -40°C / -40°F) of MOTUL DOT 5.1 is lower than DOT 4 (up to 1800 mm²/s) and DOT 3 (up to 1500 mm²/s) brake fluid specifications and allows easier fluid circulation and flow through the micro-valves of anti-locking systems for better response of ABS and other electronic stability programs (ESP, ASR,...) requiring quick brake systems actuation.

RECOMMENDATIONS

Oil changes: 12 to 24 months according to the manufacturers' recommendations.

For safety advice, draining once a year is recommended.

Mixable with DOT 3, DOT 4 and DOT 5.1 NON SILICONE BASE products.

Do not mix with silicone (DOT 5 silicone base) or mineral base fluids (LHM).

Store brake fluid in its original container, tightly closed to avoid absorption of moisture.

PROPERTIES

Glycol ether base.

	MOTUL DOT 5.1	DOT 5.1 Specifications
Colour	Yellow	
Dry boiling point	267°C / 512°F	260°C / 500°F minimum
Wet boiling point	188°C / 370°F	180°C / 356°F minimum
Viscosity at - 40°C (- 40°F)	830 mm ² /s	900 mm ² /s maximum
Viscosity at 100°C (212°F)	1.8 mm ² /s	1.5 mm ² /s minimum

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. - Made in France

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - Web Site: www.motul.com

01/24