



## MOTUL E TEC 4T LUB 10W-30

Lubricant for HONDA 4-stroke motorbikes  
100% Synthetic

### TYPE OF USE

100% Synthetic high performance lubricant specially designed for HONDA motorbikes : street and road bikes, trails, off-road bikes, enduro,..., fitted with 4 stroke engines, integrated gearbox or not, wet or dry clutch; engines requiring a low viscosity grade, engines meeting Euro 5 emission regulation, fitted with exhaust gas after treatment systems: catalytic converters, air injection into exhaust pipe,...

Other uses: street bikes without catalytic converter, scooters, maxi-scooters,...

Must be use only when manufacturers recommend this type of lubricant. When in doubt, always refer to the owner's manual.

### PERFORMANCES

STANDARDS	API SL Honda Japan No FR MOT 2022-00359
-----------	--

PERFORMANCES	JALOS MA N° M033HMC372
--------------	------------------------

Lubricant developed in Japan in collaboration with HONDA engineers to meet their latest engine specifications.

100% synthetic lubricant, result of the Research and Development between HONDA and MOTUL:

- Optimization of engine response and driving experience.
- Viscosity grade 30 at hot temperature and dedicated technology, allowing to reduce fuel consumption of HONDA motorcycles and therefore to limit CO<sub>2</sub> emissions (EURO 5 compatible). Reduction of oil consumption.
- JASO MA approved for perfect operation of wet clutches.
- Very high shear strength of the oil film at high temperatures for maximum engine and gearbox protection. Smoother gear changes.
- High oil performance over the entire oil change interval.
- Reduced Phosphorus and Sulphur content to ensure the perfect operation and longevity of the catalytic converters, necessary to meet the latest emission standards.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - [www.motul.com](http://www.motul.com)

[motul.com](http://motul.com)

10/22



## MOTUL E TEC 4T LUB 10W-30

Lubricant for HONDA 4-stroke motorbikes  
100% Synthetic

### RECOMMENDATIONS

Drain interval: refer to manufacturers' recommendations and tune to your own use.  
Can be mixed with synthetic or mineral oils.

### PROPERTIES

Viscosity grade	SAE J 300	5W-30
Density at 20°C (68°F)	ASTM D1298	0.850
Viscosity at 40°C (104°F)	ASTM D445	65.6 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	10.5 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	150.0
Pour point	ASTM D97	-36.0 °C / -33.0 °F
TBN	ASTM D2896	8.8 mg KOH/g
Flash point	ASTM D92	230.0 °C / 446.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.