

**Lubricant for HONDA motorbikes
100% Synthetic**

TYPE OF USE

100% Synthetic high performance lubricant specially designed for HONDA motorbikes : street and road bikes, trails, off-road bikes, enduro,..., fitted with 4 stroke engines, integrated gearbox or not, wet or dry clutch; engines requiring a low viscosity grade, engines meeting Euro 2 or Euro 3 emission regulation, fitted with exhaust gas after treatment systems : catalytic converters, air injection into exhaust pipe,...

Other uses : street bikes without catalytic converter, scooters, maxi-scooters,...

Must be use only when manufacturers recommend this type of lubricant. When in doubt, always refer to the owner's manual.

PERFORMANCES

STANDARDS API SJ

PERFORMANCES JALOS MA under N°M033MOT082, HONDA MOTORCYCLES JAPAN under N°EU MOT
2009-00127

High performance engine oil developed in Japan with HONDA R&D engineers in order to meet the most stringent requirements of HONDA motorbikes.

100% Synthetic lubricant, result of the research and development between HONDA and MOTUL:

- Viscosity grade 30 at high temperature with dedicated technology, for improved fuel consumption of HONDA motorbikes and therefore CO₂ emission reduction. Provides oil consumption reduction.
- Low Phosphorus and Sulfur content for better operating conditions and duration of catalytic converters required to meet the latest emission regulations.
- Viscosity grade 10W at cold temperature for better engine wear protection during cold start and optimal anti-wear protection to ensure gears life time.
- Increase oil film shear resistance at high temperature for better gearbox protection and smoother gearshift.
- Specific additivation for perfect metallic material compatibility with HONDA gearboxes and wet clutches design to insure optimal protection.
- JASO MA approved to guarantee a perfect lock up of wet clutch.



E TEC LUB 4T 10W-30

Lubricant for HONDA motorbikes
100% Synthetic

RECOMMENDATIONS

Drain interval: refer to manufacturers' recommendations and tune to your own use.
Can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	10W-30
Density at 20°C (68°F)	ASTM D1298	0.856
Viscosity at 40°C (104°F)	ASTM D445	65.6 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	10.1 mm ² /s
Viscosity Index	ASTM D2270	139.0
Pour point	ASTM D97	-30.0 °C / -22.0 °F
TBN	ASTM D2896	8.2 mg KOH/g
Flash point	ASTM D92	240.0 °C / 464.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br\>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com