



ECO-TECH 5W-30

Fuel Economy Gasoline Engine Lubricant

100% Synthetic

TYPE OF USE

100% Synthetic Fuel Economy engine oil specially formulated to provide ultimate level of power especially for recent gasoline engine designs. Suitable for turbocharged or naturally aspirated, direct or indirect injection, gasoline engines equipped with catalytic converters.

Suitable for all gasoline engines using leaded or unleaded gasoline, LPG, Autogas fuel. E85 fuel compatible.

All driving conditions: City, Road, Highway.

PERFORMANCE

STANDARDS API SERVICE SP
 ILSAC GF-6A

Designed to meet the new API SP and ILSAC GF-6A specifications. API SP standard is fully backward compatible over API SN standard and all former API standards.

RECOMENDATIONS

Drain period: according to manufacturers' recommendations and driving patterns.

PROPERTIES

Viscosity grade	SAE J 300	5W-30
Density at 20°C (68°F)	ASTM D4052	0.848
Viscosity at 40°C (104°F)	ASTM D445	65.1 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	10.7 mm²/s
Viscosity index	ASTM D2270	157
TBN	ASTM D2896	7.0 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 – Tel : 33 1 48 11 70 00 – Fax : 33 1 48 33 28 79 – Web Site: www.motul.fr

04/25