

FORK OIL FL LIGHT 5W

**High Performance Hydraulic Fluid for any telescopic fork
100% Synthetic
LIGHT**

TYPE OF USE

Synthetisches Gabelöl auf Ester-Basis für alle Arten von Motorradgabeln
(Standard, USD, Cartridge) geeignet. Empfohlen für den Einsatz im Rennsport.

PERFORMANCES

Reduced internal friction, specially fork tubes and seals thanks to the exclusive anti-friction additive designed and developed by MOTUL.
Outstanding suspension performance as soon as riding and maintained performance in time.
High performance anti-foam avoiding air transfer to the air chamber to maintain suspension performance.
Anti-wear and extreme pressure properties. Anti-corrosion. Seals protection.

RECOMMENDATIONS

MOTUL Fork Oil Factory Line can be mixed to obtain the required absorption effect.
Use the exact quantity recommended by the fork manufacturer.

PROPERTIES

| | | |
|---------------------------|------------|-------------------------|
| Grade de viscosité | | 5W |
| Densité à 20°C | ASTM D1298 | 0.834 |
| Viscosité à 40°C (104°F) | ASTM D445 | 18.0 mm ² /s |
| Viscosité à 100°C (212°F) | ASTM D445 | 4.0 mm ² /s |
| Indice de viscosité | ASTM D2270 | 121.0 |
| Point d'écoulement | ASTM D97 | -39.0 °C / -38.0 °F |
| Point éclair | ASTM D92 | 208.0 °C / 406.0 °F |

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 -