

**2 Stroke Engine Oil for Motorised Garden Tools
Technosynthese®**

TYPE OF USE

Specially formulated for 2 Stroke engine garden tools.

Motor cultivator, chain saw, lawn mower, ground clearing machine...

Recommended for engines working under severe conditions or at high engine speeds.

Suitable with leaded or unleaded gasoline.

PERFORMANCES**STANDARDS****API TC**

Pre-diluted lubricant which mixes instantaneously with gasoline and remains stable.

Reinforced anti-rust and anti-corrosion properties.

Reduces deposits in exhaust pipes and on pistons.

Prevents spark plug from fouling.

RECOMMENDATIONS

Premix ratio : from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements.

PROPERTIES

Color	Visual	Red
Density at 20°C (68°F)	ASTM D1298	0.880
Viscosity at 40°C (104°F)	ASTM D445	79.2 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	10.0 mm ² /s
Viscosity Index	ASTM D2270	107.0
Pour point	ASTM D97	-15.0 °C / 5.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



GARDEN 2T

**2 Stroke Engine Oil for Motorised Garden Tools
Technosynthese®**

Flash point

ASTM D92

178.0 °C / 352.4 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com