

GARDEN 4T 10W-30

**4 Stroke Engine Lubricant for Motorized Garden Tools
Gasoline and Diesel Engine
Technosynthese® - SAE 10W-30**

TYPE OF USE

Specially formulated for motorized garden tools and small farming equipment.

All Gasoline and Diesel 4 stroke engines, naturally aspirated or turbocharged.

Lawn mowers, motor mowers, ride on mowers, tillers, light tractors,...

Suitable for all types of fuel: leaded and unleaded gasoline, Diesel fuel, Ethanol, biofuels.

All types of 4 stroke engines with or without catalytic converter.

PERFORMANCES

STANDARDS API SJ / SH / CF

Technosynthese® lubricant reinforced with synthetic base stocks for improved engine protection

Ensures the engine cleanliness

Protection during wintering

Dispersant and detergent properties

Good cold starting, perfectly stable in a hot engine

Anti-wear, Anti-oxidation properties

Anti-corrosion, Anti-foam properties

RECOMMENDATIONS

Oil change: According to manufacturers' requirements and adjust according to your own use.

MOTUL GARDEN 4T SAE 10W-30 can be mixed with synthetic or mineral lubricants.

PROPERTIES

Viscosity grade	SAE J 300	10W-30
Density at 20°C (68°F)	ASTM D1298	0.872

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



GARDEN 4T 10W-30

**4 Stroke Engine Lubricant for Motorized Garden Tools
Gasoline and Diesel Engine
Technosynthese® - SAE 10W-30**

Viscosity at 40°C (104°F)	ASTM D445	70.3 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	10.6 mm ² /s
Viscosity Index	ASTM D2270	141.0
Pour point	ASTM D97	-33.0 °C / -27.0 °F
TBN	ASTM D2896	10.3 mg KOH/g
Flash point	ASTM D92	226.0 °C / 439.0 °F