

GARDEN 4T 10W-40

**4 Stroke Engine Lubricant for Motorized Garden Tools
Gasoline and Diesel Engines
Technosynthese® - SAE 10W-40**

TYPE OF USE

Specially formulated for motorized garden tools and small farming machines.

All Gasoline and Diesel 4 stroke engines, naturally aspirated or turbocharged.

Lawn mowers, ride on mowers, light tractors, tillers, small generators...etc.

Suitable for all types of fuels: leaded and unleaded gasolines, Diesel fuels, Ethanol, biofuels.

All types of 4 stroke gasoline engines with or without catalytic converter.

PERFORMANCES**STANDARDS**

API SM / CF

High Performance Technosynthese® multigrade lubricant reinforced with synthetic base stocks for improved engine protection.

Excellent engine protection at high temperature.

Easy cold start.

Ensures the engine cleanliness.

Protection during wintering.

Dispersant and detergent properties.

Anti-wear, Anti-oxidation properties.

Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Oil change: According to manufacturers' requirements and adjust according to your own use.

MOTUL GARDEN 4T SAE 10W-40 can be mixed with synthetic or mineral lubricants.



GARDEN 4T 10W-40

**4 Stroke Engine Lubricant for Motorized Garden Tools
Gasoline and Diesel Engines
Technosynthese® - SAE 10W-40**

PROPERTIES

Viscosity grade	SAE J 300	10W-40
Density at 20°C (68°F)	ASTM D1298	0.861
Viscosity at 40°C (104°F)	ASTM D445	102.3 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	15.1 mm ² /s
Viscosity Index	ASTM D2270	152.0
Pour point	ASTM D97	-36.0 °C / -33.0 °F
TBN	ASTM D2896	10.4 mg KOH/g
Flash point	ASTM D92	228.0 °C / 442.0 °F